Form 3160-5 (June 1990)

UNITED STATES DEPARTN IT OF THE INTERIOR BUREALLOE LAND MANAGEMENT

N.M. Oil Con		Division
311 S. 1s.	٠.	

O/W

		Al state, con-	Expires March 31, 1993
SUNDRY NOTICES	AND REPORTS ON W	ÆĽLS	5. Lease Designation and Serial No.
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.			LC-029395-B
Use "APPLICATION FO	OR PERMIT—" for such	proposals	6. If Indian, Allottee or Tribe Name
SUBMIT	IN TRIPLICATE	4	
		- 18 in the	7. If Unit or CA, Agreement Designation
l. Type of Well ☑ Oil ☐ Gas ☐ Other		Droru.	1.24
Well Well Other		RECEIVED	8: Well Name and No.
2. Name of Operator DEVON ENERGY CORPORATION (NEVA	DAY	/E OOD ARTESIA	A ":-/
· · · · · · · · · · · · · · · · · · ·		\C_{\delta}.	Turner "B" #136
3. Address and Telephone No.			9. API Well No.
20 NORTH BROADWAY, SUITE 1500, OK	LAHOMA CITY, OKLAHOMA	73102 (405) 236-3671	30-015-29622
Location of Well (Footage. Sec., T., R., M., or Survey De	escription)		10. Field and Pool, or Exploratory Area
1521' FSL & 146' FEL, Sec. 20-17S-31E			Grayburg Jackson
		11. County or Parish, State	
			Eddy County, NM
CHECK APPROPRIATE BOX(s) TO INDICATE NATU	JRE OF NOTICE, RE	PORT, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTIO	
		7.7.2.07.7.07.70	
Notice of Intent	Abandonment		Change of Plans
	Recompletion		New Construction
Subsequent Report	Plugging Back		Non-Routine Fracturing
Final Abandonment Notice	Casing Repair Altering Casin		Water Shut-Off
		TD'd & set casing	Conversion to Injection Dispose Water
	Z Culci Spud, 1	Du de set castilg	(Note: Report results of multiple completion on Well
3. Describe Proposed or Completed Operations (Clearly state all pe	rtinent details, and give pertinent dates.	including estimated date of starting at	Completion or Recompletion Report and Log form.) Ty proposed work. If well is directionally drilled give subsurface
locations and measured and true vertical depths for all market		· ·	,
Spud well @ 1:00 p.m. 9/2	<i>1</i> 9/97.		
• •	s follows: 10 jts 8 5/8	". 24#. J-55. ST&C. 8	3rd: set @ 440'
_	•		6% gel, 2% CaCl2 & ¼ #/sk
			C" w/2% CaCl2, (wt 14.8 ppg, yield
1.32 сп/sk). Сп	rc'd cement to surface	e.	
Reached TD of 3925'.			
	n g as follows: 86 jts 5	½", 15.5#, J-55, LT&	&C set @ 3924', float collar @
3886'.			
Cemented casing as t	follows: <u>Lead</u> – 975 s	xs 35/65 Lite "C" w/4	1% gel, 5% salt & 1/4 #/sk celloflake,
(wt. 13.05 ppg, v	yield 1.75 cft/sk, H2O	9.19 GPS). Tail – 30	00 sxs "H" w/10% gypsum, 5% salt &
			GPS). Circ'd cement to surface.
	, (FP 6,)	,	(1 5). (11 t t t t t t t t t t t t t t t t t t
4. I hereby certify that the foregoing is true and correct			
	Karen	Byers	1 1
ligned Kanam Bulso		eering Technician	Date /0/8/97
This space for Federal or State office use)			
V			• •
Approved by	Title		Date
Conditions of approval, if any:			

RECEIVED

JUREAU OF LAND MGMT. ROSWELL OFFICE