


DRILLING CONTROL
CONDITION IV-B-5000 PSI WP



DRILLING CONTROL

MATERIAL LIST - CONDITION IV - B

- | | |
|--------------------|--|
| A | Texaco Wellhead |
| B | 5000# W.P. drilling spool with a minimum 2" flanged outlet for kill line and 3" minimum flanged outlet for choke line. |
| C | 5000# W.P. Dual ram type preventer, hydraulic operated with 1" steel, 5000# W.P. control lines. |
| D | 5000# W.P. Annular preventer, hydraulic operated with 1" steel, 3000# W.P. control lines. |
| E | Rotating Head with fill up outlet and extended Blosse line. |
| 1,2,4,5,8,10,11,12 | 2" minimum 5000# W.P. flanged full opening steel gate valve, or Halliburton Lo Torc Plug valve. |
| 3 | 2" minimum 5000# W.P. back pressure valve. |
| 6,9 | 3" minimum 5000# W.P. flanged full opening steel gate valve, or Halliburton Lo Torc Plug valve. |
| 7 | 3" minimum 5000# W.P. flanged hydraulic valve |
| 15 | 3" minimum Schedule 160, Grade B, seamless line pipe |
| 16 | 2" minimum x 3" 5000# W.P. flanged cross |
| 13,14 | 2" minimum 5000# W.P. adjustable chokes with carbide trim. |
| 17 | Cameron Mud Gauge or equivalent (location in choke line optional). |
| 18 | 6" minimum 1000# hydraulic flanged valve. |
| 24 | 8" minimum steel flow line. |
| 25 | 2" minimum 3000# W.P. flanged or threaded full opening steel gate valve, or Halliburton Lo Torc Plug valve. |



TEXACO, INC.
 MIDLAND DIVISION
 MIDLAND, TEXAS



EXHIBIT D

30-015-29720

CTB-474
7-31-98

12-2-97
LL-MCFE-GR
4650-12302
Comp-GR
4650-12302
DeH-Neut-
Nat GR
200-12302

CTB-474
7/27/99

ESSELE

Oxford®

NO. R753 1/3

10%



Texmack II Federal #1

Ut. C NE NT

NC Depo KEM 12-11-97

Rust.	642	WC	9875
Sal.	820	Penn.	10498
BK	1702	Stm	11131
Jamil	1826	at.	11464
ytd	1960	mulet	11676
7-Riv	2282	MC	11923
Qn.	2848	TD	MC 12359
Gabg	3328		
GP	3642		
Glor.	5145		
ytd	5226		

Handwritten text at the top of the page, possibly a title or header.