

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.

30-015-30162

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil / Gas Lease No.

7. Lease Name or Unit Agreement Name

TEXMACK 2 STATE COM

8. Well No.

1

9. Pool Name or Wildcat

FREN

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMI
(FORM C-101) FOR SUCH PROPOSALS.

1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
TEXACO EXPLORATION & PRODUCTION INC.

3. Address of Operator
P.O. Box 2100, Denver Colorado 80201

4. Well Location

Unit Letter O : 660 Feet From The SOUTH Line and 1650' Feet From The EAST Line

Section 2 Township 17-S Range 31-E NMPM EDDY COUNTY

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPERATION ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

PRODUCTION CASING ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. DRILLED 7 7/8 INCH HOLE TO 12430'.
2. RU SCHLUMBERGER. LOG W/PLATFORM EXP. LOGS STOPPED @ 12366'. LOG TO BOTTOM OF INTERMEDIATE CSG @ 4497'
3. RAN 86 JOINTS OF 5 1/2 INCH, 17#, M-95 AND 209 JOINTS OF 5.5, 17#, WC-70 LTC CASING SET @ 8931' W/FLOAT SHOE, FLOAT COLLAR, AND DV TOOL (5'). TOTAL OF 12437'. SET @ 12430' KB. 06-30-98.
4. DOWELL CEMENTED BOTTOM STAGE WITH 820 SX 50/50 POZ CLASS H W/1% D20, 5% D44, 1/4# SX D29, .1% D13. 1.35 YIELD, 197 BBL SLURRY 14.2 WT. DID NOT CIRC CMT TO PITS.
DOWELL CEMENTED THE TOP STAGE W/261 SACKS 35/65 POZ CLASS H W/6% D20, 5% D44, 1/4# SX D29, 2.14 YIELD, 100 BBL SLURRY, 12.4 WT. FOLLOWED BY 1134 SX 50/50 POZ CLASS H W/2% D20, 5% D44, 1/4# SX D29, 1.35 YIELD, 273 BBL SLURRY, 14.2 WT. BUMP PLUG AND CLOSED DV TOOL WITH 3500 PSI.
5. ND. RELEASE RIG @ 6:00 AM 07-01-98.
6. PREP TO COMPLETE.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE C. P. Zarkem / SIKH TITLE Eng. Assistant.

DATE 7/8/98

TYPE OR PRINT NAME Sheilla D. Reed-High

Telephone No. (303)793-4851

(This space for State Use)

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

**ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR**

TITLE

DATE 9-2-98