

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL:		OIL WELL ☒	GAS WELL ☐	DRY ☐	Other ☐		
b. TYPE OF COMPLETION:		NEW WELL ☒	WORK OVER ☐	DEEP-EN ☐	PLUG BACK ☐	DIFF. REVR. ☐	Other ☐
2. NAME OF OPERATOR						3. ADDRESS OF OPERATOR	
BURNETT OIL CO., INC.						801 CHERRY STREET, SUITE 1500 FORT WORTH, TEXAS 76102 (817/332-5108)	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)						5. LEASE DESIGNATION AND SERIAL NO.	
At surface UNIT A 660' FNL, 680' FEL						LC029338A	
At top prod. interval reported below SAME AS SURFACE						6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
At total depth						7. UNIT AGREEMENT NAME	
14. PERMIT NO.						8. FARM OR LEASE NAME	
3160-3						GISSLER A	
15. DATE SPUDDED						9. WELL NO.	
6/24/98						16 (30-015-30275)	
16. DATE T.D. REACHED						10. FIELD AND POOL, OR WILDCAT	
7/3/98						LOCO HILLS PADDOCK	
17. DATE COMPL. (Ready to prod.)						11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA	
9/28/98						SEC 23, T17S, R30E	
18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*						12. COUNTY OR PARISH	
3674' GL						EDDY	
19. ELEV. CASINGHEAD						13. STATE	
						NM	

20. TOTAL DEPTH, MD & TVD	21. PLUG, BACK T.D., MD & TVD	22. IF MULTIPLE COMPL., HOW MANY*	23. INTERVALS DRILLED BY	ROTARY TOOLS	CABLE TOOLS
5502'	5457'			X	
24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*					25. WAS DIRECTIONAL SURVEY MADE
4548'-4565' & 4786'-4898' PADDOCK (GLORIETA)					NO
26. TYPE ELECTRIC AND OTHER LOGS RUN					27. WAS WELL CORED
COMPENSATED NEUTRON/GR, MICRO-CFL/GR AZIMUTHAL LATEROLOG, CBL					NO

28. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24#	491'	12 1/4"	699 SKS CLASS C	
5 1/2"	15.5	5502'	7 7/8"	TTL 1325 SKS CLASS C IN 2 STAGES	

29. LINER RECORD					30. TUBING RECORD		
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 7/8"	4656'	

31. PERFORATION RECORD (Interval, size and number)	32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.
4786', 4812'-17', 4851', 4860', 4864'-66', 4868', 4871', 4884', 4886', 4888', 4890', 4894', 4898'. TOTAL 20 HOLES @ 1 SPF WITH 4" CASING GUN. 4548'-4565' 2SPF total 32 holes w/4" casing gun.	DEPTH INTERVAL (MD) AMOUNT AND KIND OF MATERIAL USED
	4786'-4898' 4126 GALS 15% HCL ACID
	4786'-4898' 490 bbls 20% HCLw/30 GPT Ultra gel
	4548'-4565' 462 gal 7 1/2% HCL % 402 bbl YF13C
	4548'-4565' frac w/39,890# 20/40 sand. 500 gal

33.* PRODUCTION " " 7 1/2% HCL							
DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
7/16/98		PUMPING SUBMERSIBLE TYPE PUMP				PRODUCING	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
10/02/98	24			37	76	913	
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)		35. LIST OF ATTACHMENTS	
SOLD TO CONOCO		CN/GR, MICRO-CFL/GR AZIMUTHAL LATEROLOG STATE OF N.M.—INCLINATION REPORT	

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED Hurling Land TITLE PETROLEUM ENGINEER DATE 10/12/98

(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

38. GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
GLORIETA	4786'	4898'	SOME OIL, LOTS OF WATER, SOME GAS ALL DOLOMITE.	ANHYDRITE SALT BASE OF SALT YATES SEVEN RIVERS RED SAND GRAYBURG SAN ANDRES GLORIETA	175' 450' 1125' 1294' 1617' 2245' 2649' 3006' 4472'	

RECEIVED

OCT 15 '98

BLA NM
ROSW