

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1 Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2 Name of Operator

Mack Energy Corporation

3 Address and Telephone No.

P.O. Box 960, Artesia, NM 88211-0960

(505)748-1288

4 Location of Well (Footage, Sec., T. R., M. or Survey Description)

1710 FNL 330 FWL Sec 29 T17S R29E

5 Lease Designation and Serial No.

NM-29281

6 If Indian, Allottee or Tribe Name

7 If Unit or CA, Agreement Designation

8 Well Name and No.

Schley Federal #7

9 API Well No.

30-015-30303

10 Field and Pool, or Exploratory Area

East Empire Yeso

11 County or Parish, State

Eddy, NM

12 CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Completion  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)\*

11/11/98 Drill out DV Tool @ 3755'. RIH & clean out to 5091'.

11/13/98 Perfed casing @ 4680-4799' 22 holes, 4648-4650' 3 holes, 4535-4544' 4 holes, 4472-4479' 16 holes. Acidize perfs 4680'-4799' w/1000 gals 15% NEFE acid.

11/14/98 Acidize perfs 4648'-50' w/250 gals 15% NEFE acid.

11/16/98 Acidize perfs 4535-44' w/500 gals 15% NEFE acid. Acidize perfs 4472'-4479' w/500 gals 15% NEFE acid.


11/17/98 Frac perfs 4648-4799' w/31,082 gals 30# gel & 62,000 lbs 16/30 Ottawa Sand.

11/18/98 ReAcidize perfs 4535-44' w/1000 gals 15% acid w/chemicals, 1000 gals 20%, 2000 gals gelledf 20%, 1000 gals 20%, 2000 gals gelled 20%, 1000 gals 20%. Flush w/1200 gals 2% KCL.

11/19/98 Frac Perfs 4472-4479' w/84,400# White Ottawa Sand 16/30, 32,000 gals gell.

11/20/98 Ran in hole w/2 7/8" tubing seat nipple at @ 4838'.

11/21/98 RIH with 2 1/2 x 2 x 16' pump, 188-7/8" rods, Waiting on pumping unit Lufkin 320.



14. I hereby certify that the foregoing is true and correct

Signed Wesley D. Cuth

Title Production Clerk

Date 12/23/98

(This space for Federal or State office use)

Approved by \_\_\_\_\_

Conditions of approval, if any: \_\_\_\_\_

Title \_\_\_\_\_

Date \_\_\_\_\_

RECEIVED  
MAY 23 98