

- position.
4. Kelly equipped with Kelly cock.
 5. Inside blowout preventer or its equivalent on derrick floor at all times with proper threads to fit pipe being used.
 6. Kelly saver-sub equipped with rubber casing protector at all times.
 7. Plug type blowout preventer tester.
 8. Extra set pipe rams to fit drill pipe in use on location at all times.
 9. Type RX ring gaskets in place of Type R.

MEC TO FURNISH:

1. Bradenhead or casinghead and side valves.

Valves must be full opening and suitable for high pressure mud service.

3. Controls to be of standard design and each marked, showing opening and closing position.
4. Chokes will be positioned so as not to hamper or delay changing of choke beans. Replaceable parts for adjustable choke, other bean sizes, retainers, and choke wrenches to be conveniently located for immediate use.
5. All valves to be equipped with hand-wheels or handles ready for immediate use.
6. Choke lines must be suitably anchored.

11. Do not use kill line for routine fill-up operations.

30-015-30307

OGRID 13837

PROP 22367

2001 96610

6-21-99

PLATTMAN EXHIBITS/S-D LIND-DAVARTY
COMBUSTED NEUTRON/INST

200' - 5,154'

PLATTMAN EXHIBITS/AZIMUTHAL LATEROLOG
MINED-CFL INST

70' - 5,146'

NSL: 4058-ACSD
10/16/98

Oxford®

ESSELTE

NO. R753 1/3

10%



Geol. Tops per 136A

Yates	786
Trivens	1040
Queen	1648
Grayburg	
San Andres	2351
Levington Sand	2423
Glorieta	3794

THE UNIVERSITY OF CHICAGO