

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1 Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2 Name of Operator

Mack Energy Corporation

3. Address and Telephone No.

P.O. Box 960, Artesia, NM 88211-0960

(505)748-1288

4. Location of Well (Footage, Sec., T. R., M. or Survey Description)

1980 FSL 430 FEL Sec 22 T17S R30E

5. Lease Designation and Serial No.

LC-029020-G

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Dexter #9

9. API Well No.

30-015-30328

10. Field and Pool, or Exploratory Area

Loco Hills Paddock

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud & Cement Casing
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)*

11/07/98 MIRU L&M Rig #3, Spud 17 1/2" hole at 4:00pm, lost returns at 184'.

11/08/98 TD 17 1/2" hole at 450' at 6:00am. RIH with 9 Joints 13 3/8" 48# K-55 ST&C casing Landed @ 446'. BJ Service Cement w/525sx Class C 2% CaCl, Plug down 11:00am did not circ, J.Amos with BLM witness, ready mix to surface. WOC 12 hours, 11:30pm drilling 12 1/4" hole.

11/09/98 TD 12 1/4" hole @11:30am, RIH with 28 jts 8 5/8" 24# K-55 ST&C casing Landed @ 1196', BJ Service cement with lead 450sx BJ lite tail in 250sx Class C 2% CaCl, plug down at 5:00pm, circ 165sx to pit.

ORIG. SGD. GARY GOURLEY

ACCEPTED FOR RECORD

NOV 27 1998

SLM

14. I hereby certify that the foregoing is true and correct

Signed

Cissa D. Carter

Production Clerk

Date

11/17/98

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

RECEIVED

NOV 18 '98

ELM
ROSWELL, NM