

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Mack Energy Corporation

3. Address and Telephone No.

P.O. Box 960, Artesia, NM 88211-0960 (505)748-1288

4. Location of Well (Footage, Sec., T. R., M. or Survey Description)

Sec-22 17S-R30E 2310 FNL & 1650 FWL

5. Lease Designation and Serial No.

NM-0467930

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Sinclair Parke #2

9. API Well No.

30-015-30329

10. Field and Pool, or Exploratory Area

Loco Hills Paddock

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud & Cement Casings
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

6/26/2000 Spud 17 1/2" hole 6-25-00 (called BLM). TD hole 471' 10AM, RIH csg had hard spot, pipe would not go (called BLM Gary Gourley @ Roswell ask for OK to set pipe at 296' got OK. Ran 13 3/8" 7 joints K-55 48# STC @ 296', C/w 450sx Class C 2% CaCl, plug down 6:00 pm circ 65sx. WOC 12 hours.
6/27/2000 TD hole 11:30 PM @ 1090' (notified BLM Duncan).
6/28/2000 RIH w/8 5/8" 24# J-55 24 joints ST&C @ 1078', C/w 275sx 35/65/6, 5# salt 1/4# CF, tail in w/200sx Class C 2% CaCl, plug down 4:30 AM circ 10sx. cement fell back, ready mix to top. Drilling 7-7/8" hole @ 4:30 p.m.
7/06/2000 TD @ 5181', could not get past 1137'.
7/07/2000 RIH with reamers work area at 1137' and run to bottom.
7/08/2000 Got to bottom with logs, at 5121', run PE, HALS, NGT, POH.
7/09/2000 RIH w/5 1/2" 17# 116 joints LT&C J-55 @ 5142', Cemented 1st stage w/180sx 50/50/2 Poz 5# salt 5/10% FL20, circ 32sx plug down 9:15 PM. WOC 6 hours.
7/10/2000 Cemented 2nd stage w/575sx 35/65/6 3# salt 1/4# CF, tail in w/250sx 50/50/2 5# salt 5/10% FL20, plug down 5:00 AM, release rig.

JUL 18 2000 (ORIG. SGD.) GARY GOURLEY

14. I hereby certify that the foregoing is true and correct

Signed

Gary Gourley

Title

Production Analyst

Date

7/12/00

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

RECEIVED
JUL 13 A 9:35
HOSPITAL CENTER
TOLSON