

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1 Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2 Name of Operator

Mack Energy Corporation

3 Address and Telephone No.

P.O. Box 960, Artesia, NM 88211-0960

4 Location of Well (Footage, Sec., T. R., M. or Survey Description)

2035 FNL 2450 FWL Sec 29 T17S R29E

5 Lease Designation and Serial No.

NM-29281

6 If Indian, Allottee or Tribe Name

7 If Unit or CA, Agreement Designation

8 Well Name and No.

Schley Federal #6

9 API Well No.

30-015-30459

10 Field and Pool, or Exploratory Area

East Empire Yeso

11 County or Parish, State

Eddy, NM

12 CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud & Cement Casing
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)*

11/23/98 Spud 17 1/2" hole 3:00pm (called BLM J.Amos) lost returns at 102'. Got back full returns at 134', TD hole at 297'.

11/24/98 Ran 6 jts 13 3/8" 48# K-55 ST&C New casing, rig up BJ Service pump 325sx Class C 2% CaCl, circ 18sx to pit, plug down 2:15am, WOC 12 hours.

11/25/98 TD 12 1/4" hole 4:00am (Called BLM), circ hole clean, POH, rig up csg crew run 8 5/8" 21 jts ST&C K-55 24# set at 881', rig up BJ Service cement with 250sx 35/65 Lite 6% gel 1/4# CF 3# salt, tail in with 200sx Class C 2% CaCl, circ 90sx to pit, plug down 8:30am. WOC.

APPROVED
12/22/98
acs

14 I hereby certify that the foregoing is true and correct

Signed

Cristina D. Costa

Title

Production Clerk

Date

12/22/98

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

RECEIVED
DEC 23 98
BLM
ROBERT, NM