

ENRON OIL & GAS COMPANY
CONOCO "9" STATE COM NO. 1
API 30-015-30690
PAGE 2 OF C-103
10/11/99

8/7/99

Cement plug 10,488-10,388'. 100' plug, cement pumped – 40 sx Premium Class "H", 16.4#/gal, 1.06 cu ft/sk

Cement plug 8620-8520'. 100' plug, cement pumped – 45 sx Premium Class "H", 16.4#/gal, 1.06 cu ft/sk

Cement plug 7230-7138. 92' plug, cement pumped – 40 sx Premium Class "H", 16.4#/gal, 1.06 cu ft/sk

Cement plug 6014-5914'. 100' plug, cement pumped – 45 sx Premium Class "H", 16.4#/gal, 1.06 cu ft/sk.

Cement plug 3900-3800'. 100' plug, cement pumped – 40 sx Premium Class "H", 16.4#/gal, 1.06 cu ft/sk.

Cement plug 2700-2600'. 100' plug, cement pumped 30 sx Premium Plus "C", 15.6#/gal, 1.18 cu ft/sk.

Pulled 5 stds DP. Waited on cement two (2) hrs – tagged cement at 2,600' with 8000# wt.

Cement plug 489-389'. 100' plug, cement pumped 25 sx Premium Plus "C", 15.6#/gal, 1.18 cu ft/sk.

Cement plug 50' – surface. 50' plug, cement pumped 15 sx Premium Plus "C", 15.6#/gal, 1.18 cu ft/sk.

8/8/99

Nipple down BOP. Install dry hole marker.