

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
811 South First, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised March 25, 1999

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

WELL API NO.  
30-015-30919

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:  
STATE '20-B'

8. Well No.

2

9. Pool name or Wildcat (28509)  
Grayburg Jackson-7R's, QN,GB,SA

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

1. Name of Operator

Clayton Williams Energy, Inc.

2. Address of Operator

Six Desta Drive, Suite 3000, Midland, Texas 79705

3. Well Location

Unit Letter H : 2285 feet from the North line and 330 feet from the East line

Section 20 Township 17S Range 29E NMPM County Eddy

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3602' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

1/26/00: Spud 17-1/2" hole at 2300 hrs. Drilling Contractor: Norton Drilg. Co., Rig #157.

1/27/00: Drill 17-1/2" hole to 338'. Ran 9 jts. 13-3/8", 61#, K-55 ST&C casing to 338'. Cement with 140 sx. 35:65 Poz with 6% D20 + 3% S1 + 1/4#/sx. D29, follow with 200 sx. Cl. C with 2% S1 + 1/4#/sx. D29. Circulate 35 sx. cement to surface. WOC

1/29/00: Drill 11" hole to 828'. Ran 18 jts. 8-5/8", 24#, K-55 ST&C casing to 828'. Cement with 120 sx. 35:65 Poz + 6% D-20 + 3% S1 + 1/4#/sx. D29, follow with 150 sx. 25/75 Poz + 2% S1 + 1/4#/sx. D29. Circulate 30 sx. cement to surface. WOC Test casing and BOP's to 1000 psi.

Please note WOC Time  
34

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE John F. Kennedy TITLE Drilling Manager DATE 01-31-2000

Type or print name John F. Kennedy Telephone No. (915) 682-6324

(This space for State use)

APPROVED BY Jim W. Green TITLE District Supervisor DATE 2-5-00

Conditions of approval, if any: