State of New Mexico **Submit 3 Copies** Form C-103 to Appropriate Enc., Minerals and Natural Resources Department Revised 1-1-89 District Office <u>ISTRICT I</u> .O. Box 1980, Hobbs NM 88240 OIL CONSERVATION DIVISION WELL API NO. 2040 South Pacheco 30-015-30940 STRICT II I South First, Artesia, NM 88210 Santa Fe, New Mexico 87505 5. Indicate Type of Lease STATE 🛛 FEE 🗌 DISTRICT III 1000 Rio Brazos Rd, Aztec, NM 87410 6. State Oil & Gas Lease No. E-742 SUNDRY NOTICES AND REPORTS ON WE (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN PARTY DIFFERENT RESERVOIR. USE "APPLICATION FOR PE 7. Lease Name or Unit Agreement Name (FORM C-101) FOR SUCH PROPOSALS) 1. Type Of Well: OIL GAS \boxtimes Mesquite State OTHER WEL 2. Name of Operator 8. Well No. Mack Energy Corporation 3. Address of Operator 9. Pool name or Wildcat P.O. Box 960, Artesia, NM 88211-0960 East Empire Yeso 4. Well Location North 990 West Feet From The Feet From The Line 20 17S 29E Section Eddy Township Range NMPM County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3642 RKB 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING **TEMPORARILY ABANDON** CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMEN **PULL OR ALTER CASING** CASING TEST AND CEMENT JOB OTHER: Spud & Cement Casings OTHER 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 4/18/2000 Spud 2:00 PM 17 1/2". 4/19/2000 TD 17 1/2" hole @ 3:45 AM at 352', RIH w/8 joints 13 3/8" 48 & 54# ST&C K-55, @ 346', C/w 350sClass C 2% CaCl, plug down 8:30 AM circ46sx to pit. 4/19/2000 TD 12 1/4" hole @ 810' at 3:00 PM,RIH w/ 19 joints 8 5/8" 24# ST&C J-55 set at 802', C/w 225sx 35/65/66# salt 1/4# CF, tail in w/200sx class C 2% CaCl, plug down 7:15 PM circ 101sx. WOC. 4/27/2000 10:00 PMTD 7 7/8" hole @ 4340'. 4/28/2000 RIH w/103 joints 5 1/2" 15.5#J-55 LT&C landed @ 4334', Cemented 1st stage w/150sx50-50-2 .5% FL-25 5# salt. Cemented 2nd stagew/350sx 35-65-6 1/4# CF 3# salt & 250sx 50-50-2 .5% FL-25 5# salt.Circ 73sx. Plug down 2:15 AM 4/29/2000 I hereby certify that the information above is true and complete to the best of my knowledge and belief. **Production Analyst** 5/2/00 SIGNATURE TYPE OR PRINT NAME Crissa D. Carter TELEPHONE NO. 748-1288 (This space for State Use) ORIGINAL SIGNED BY TIM W. GUM

APPROVED BY-