

Submit 3 Copies To Appropriate District Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
811 South First, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised March 25, 1999

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

WELL API NO.  
30-015-30969

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
E-4201

7. Lease Name or Unit Agreement Name:  
STATE '20 E'

7. Well No.  
1

8. Pool name or Wildcat  
Empire, East (Yeso) 96610

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well

Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
Clayton Williams Energy, Inc.

3. Address of Operator  
Six Desta Drive, Suite 3000, Midland, Texas 79705

4. Well Location

Unit Letter C : 815 feet from the north line and 2135 feet from the west line

Section 20 Township 17S Range 29E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3621' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: Amended Report to show WOC ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

2/25/00: Spud 12-1/4" hole at 1:15 p.m. 2/25/2000. Drilling Contractor: Norton Drilling Company, Rig #157.

2/25/00: Drill 12-1/4" hole to 470'. Run and set 10 jts. of 8-5/8" 24# K-55 ST&C casing, set at 463.65'. Cement with 300 sx. of Class "C" cement with 2% CaCl2 + 1/4 #/sx. Flocele. Circulate approx. 65 sx. to surface. WOC 18 hrs.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Betsy Luna TITLE Regulatory Analyst DATE 3/23/00

Type or print name Betsy Luna Telephone No. (915) 682-6324

(This space for State use)

APPROVED BY ORIGINAL SIGNED BY TIM W. GUM TITLE DISTRICT II SUPERVISOR DATE APR 03 2000  
Conditions of approval, if any: