

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

2040 South Pacheco
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.
30-015-31051

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
E4201

7. Lease Name or Unit Agreement Name:
STATE '20E'
(25339)

8. Well No.
2

9. Pool name or Wildcat (96610)
Empire, East (Yeso)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR PROPOSALS.)

1. Type of Well:
Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Clayton Williams Energy, Inc.

3. Address of Operator
Six Desta Drive, Suite 3000, Midland, Texas 79705

4. Well Location
Unit Letter C: 330 feet from the north line and 1650 feet from the west line
Section 20 Township 17S Range 29E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3627'

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: SPUD ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

5/3/00: Spud 12-1/4" hole at 12:15 a.m. 5/3/2000. Drilling Contractor: Key Energy Services, Rig #22

5/3-4/00: Drill 12-1/4" hole to 476'. Run and set 10 jts. of 8-5/8" 24# K-55 ST&C casing, set at 457'. Cement with 300 sx. of Class "C" cement with 2% CaCl2 + 1/4 #/sx. Flocele. No returns. Cement down backside with 100 sx. Cl. C + 4% CaCl2. WOC 18 hrs.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Betsy Luna TITLE Engineering Technician DATE 5/8/00

Type or print name Betsy Luna Telephone No. (915) 682-6324

(This space for State use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY _____ DATE MAY 15 2000
Conditions of approval, if any:

