

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

2040 South Pacheco
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-015-31051

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

E4201

7. Lease Name or Unit Agreement Name:

STATE '20E'

(25339)

8. Well No.

2

9. Pool name or Wildcat (96610)

Empire, East (Yeso)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK OR A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-100) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Clayton Williams Energy, Inc.

3. Address of Operator

Six Desta Drive, Suite 3000, Midland, Texas 79705

4. Well Location

Unit Letter C : 330 feet from the north line and 1650 feet from the west line

Section 20

Township 17S

Range 29E

NMPM

Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3627' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: **RIG RELEASE** ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

5/5-13/2000: Drill 7-7/8" hole to 5000'. Ran open hole logs (Platform Express/HALS) from TD to casing.

5/14/2000: Run 124 jts. 5 1/2" 17#, K-55 LT&C casing, casing set @ 4994', DV tool @ 2670'. Cement Stage I with 471 sx. Ultra Lite C + 5 pps D42 + .35% D65 + 0.35% D-156 + 0.2% D-46. Open DV tool and circulate. Circulate approx. 88 sx. cement to surface. Cement Stage II: Lead 560 sx. 35:65 Poz C + 6% D20 + 2% S1 + 1/4 pps D29. Tail with 170 sx. Cl. C neat cement. Circulate approx. 100 sx. cement to surface.

5/14/2000: Drilling rig is released. Well waiting on completion.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Betsy Luna TITLE Engineering Technician DATE 5/22/00

Type or print name Betsy Luna Telephone No. (915) 682-6324

(This space for State use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY TIM W. GUM TITLE DISTRICT II SUPERVISOR DATE JUN 01 2000

Conditions of approval, if any:

