

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

811 South First, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-015-31054

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

B6846

7. Lease Name or Unit Agreement Name:

STATE '20B'

(25235)

8. Well No.

10

9. Pool name or Wildcat (28509)

Grayburg-Jackson, 7R's, QN, SA

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Clayton Williams Energy, Inc.

3. Address of Operator

Six Desta Drive, Suite 3000, Midland, Texas 79705

4. Well Location

Unit Letter O : 990 feet from the south line and 1650 feet from the east line

Section 20

Township 17S

Range 29E

NMPM

Eddy

County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3609' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

July 26 thru August 15, 2000

1. Set RBP @ 3880' and temporarily abandon Yeso perms.
2. Perforate Lower San Andres 3518'-3738', 20 shots. Stimulate Lower San Andres.
3. Set RBP @ 3200'.
4. Perforate Upper San Andres 2446'-3075', 30 shots. Stimulate Upper San Andres.
5. Set RBP @ 2400'.
6. Perforate Grayburg Jackson 1912' - 2339', 24 shots. Stimulate Grayburg Jackson.
7. Retrieve RBP's at 3200' and 2400'. Clean out to BP at 3880'.
8. Run tubing, rods and pump.
9. Start pumping load water.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Betsy Luna TITLE Engineering Technician DATE 8/22/00

Type or print name Betsy Luna Telephone No. (915) 682-6324

(This space for State use)

APPROVED BY Jim W. Green TITLE District Supervisor DATE AUG 31 2000

Conditions of approval, if any:

