

SURFACE USE AND OPERATING PLAN  
PAGE 2

- C. No culverts, cattleguard, gates, low-water crossings, or fence cuts are necessary.
  - D. Surfacing material will consist of native caliche. Caliche will be obtained from the nearest BLM-approved caliche pit. Any additional materials that are required will be purchased from the dirt contractor.
3. Location of Existing Wells:  
Exhibit #2 shows all existing wells within a one-half mile radius of this well.
4. Location of Existing and/or Proposed Facilities:
- A. Marbob Energy Corporation has a collection facility located in Unit C of Section 18, Township 17 South, Range 31 East.
  - B. If the well is productive, a 3" plastic flowline (grade SDR 7 @ 265 psi) will be laid on the surface following the existing lease road Right-of-Way to the tank battery. Anticipated pressures in the flowline should not exceed 75 psi.
  - C. If the well is productive, power will be obtained from Central Valley Electric. Central Valley Electric will apply for ROW for their power lines.
  - D. If the well is productive, rehabilitation plans are as follows:
    - (1) The reserve pit will be back-filled after the contents of the pit are dry (within 10 months after the well is completed).
    - (2) Topsoil removed from the drill site will be used to recontour the pit area and any unused portions of the drill pad to the original natural level, as nearly as possible, and reseeded as per BLM specifications.