Form 3160-5 (June 1990)

N.M. Oil Cons. Division FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31,1993 UNITED STATES DEPARTMENT OF THE INTERIOR

5. Lease Designation and Serial No.

BUREAU OF LAND MANAGEMEN	ղ811 Տ	3 . 1	st Street	
	Artas	sia	NM 8821	1

Do not use this form for proposals to dif	Artesia, NM 88210- AND REPORTS ON WELLS ill or to deepen or reentry to a different reservoir. RPERMIT—" for such proposals	-2834 LC-029342-A 6. If Indian, Allottee or Tribe Name	
	IN TRIPLICATE	7. If Unit or CA, Agreement Designation	
I Type of Well Oil Well Well Other		8. Well Name and No.	
2. Name of Operator Mack Energy Corporation 3. Address and Telephone No.		Woolley Federal #6 9. API Well No. 30-015-31256	
P.O. Box 960, Artesia, NM 88211-0960 (505)748-1288 4. Location of Well (Footage, Sec., T. R., M. or Survey Description)		10. Field and Pool, or Exploratory Area Loco Hills Paddock	
Sec 21-T17S-R30E Surface 1564 FSL & 1838 FWL Bottom hole 2310 FSL & 2310 FWL		11. County or Parish, State Eddy, NM	
12. CHECK APPROPRIATE BOX	(s) TO INDICATE NATURE OF NOTICE, REPO	_ 	
TYPE OF SUBMISSION	TYPE OF ACTION		
Notice of Intent Subsequent Report	Abandonment Recompletion Plugging Back Casing Repair	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off	
Final Abandonment Notice	Altering Casing Other Spud & Cement Casings Other spud & Cement Casings	Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	
8/05/2000 Spud 17 1/2" hole 2:30 PM. 8/06/2000 TD 17 1/2" hole @ 9:30 AM @ 415', RIH w/13'3/8" K-55 9 joints 48# ST&C @ 404', Cemented w/450sx Class C 2% CaCl, plug down 12:30 PM circ 146sx. 8/07/2000 TD 12 1/4" hole @ 1233'. RIH w/8 5/8" 24# 27 joints ST&C J-55 @ 1226', Cemented w/350sx 35/65/6 3# salt 1/4# CF tail in w/200sx Class C 2% CaCl, plug down 8:00 PM circ 48sx. T.D. 12-1/4 hole @ 3:00 p.m. 8/15/2000 TD 7 7/8" hole 6:00 PM @ 5230' Measured depth with True Vertical Depth of 5118.7'. 8/16/2000 RIH w/5 1/2" 17# LT&C 118 joints J-55 casing @ 5193', cemented 1st stage w/150sx 50/50 Poz 2% Gel, 5/10% HL25, Cemented 2nd stage w/425sx 35/65/6 1/4# CF 3# salt tail in w/250sx 50/50/2 5/10% HL25 5# salt, plug down 6:30 AM 8/17/00 circ 78sx release rig. 8/17/00.			
14. I hereby certify that the foregoing is true and correct Signed (This space for Federal or State office use) Approved by	Title Production Analyst		
Conditions of approval, if any:			