

SURFACE USE AND OPERATING PLAN

PAGE 4

drilling operations. If a water flow is encountered, we should have ample time to line the other half of the pit with plastic before the water encroaches.

- C. Water produced from the well during completion may be disposed into the reserve pit.
 - D. Garbage and trash produced during drilling or completion operations will be hauled off. All waste material will be contained to prevent scattering by the wind. All water and fluids will be disposed of into the reserve pit. Salts and other chemicals produced during drilling or testing will be disposed into the reserve pit. No toxic waste or hazardous chemicals will be produced by this operation.
 - E. After the rig is moved out and the well is either completed or abandoned, all waste materials will be cleaned-up within 30 days. No adverse materials will be left on location. The reserve pit will be completely fenced until it has dried. When the reserve pit is dry enough to breakout and fill, the reserve pit will be leveled and reseeded as per BLM specifications. In the event of a dry hole, the location will be ripped and seeded, as per BLM Specifications, and a dry hole marker will remain.
8. Ancillary Facilities:
No airstrip, campsite, or other facilities will be built as a result of the operations on this well.
9. Well Site Layout:
- A. The drill pad layout is shown in Exhibit #4. Dimensions of the pad and pits are shown. Top soil, if available, will be stockpiled per BLM specifications as determined at the on-site inspection.
 - B. The reserve pit will be lined with a high-quality plastic sheeting.