

SURFACE USE AND OPERATING PLAN  
PAGE 2

- B. No turnouts are planned.
  - C. No culverts, cattleguard, gates, low-water crossings, or fence cuts are necessary.
  - D. Surfacing material will consist of native caliche. Caliche will be obtained from the nearest BLM-approved caliche pit. Any additional materials that are required will be purchased from the dirt contractor.
  - E. The proposed access road as shown in Exhibit #3 has been centerline flagged by John West Engineering.
3. Location of Existing Wells:  
Exhibit #2 shows all existing wells within a one-half mile radius of this well.
4. Location of Existing and/or Proposed Facilities:
- A. Marbob Energy Corporation has a collection facility located in Unit K of Section 18, Township 17 South, Range 31 East.
  - B. If the well is productive, a 3" plastic flowline (grade SDR 7 @ 265 psi) will be laid on the surface following the existing lease road Right-of-Way to the tank battery. Anticipated pressures in the flowline should not exceed 75 psi.
  - C. If the well is productive, power will be obtained from Central Valley Electric. Central Valley Electric will apply for ROW for their power lines.
  - D. If the well is productive, rehabilitation plans are as follows:
    - (1) The reserve pit will be back-filled after the contents of the pit are dry (within 10 months after the well is completed).
    - (2) Topsoil removed from the drill site will be used to recontour