

- A. Tank Battery:**
Sec. 19 wells: Sec. 19, T-17-S, R-29-E, UL G, 1980' FNL & 2310' FEL (Green B Federal #9 location)
- B. Flowlines:** See attached Property Line & Road Diagram.
5. **Location and type of Water Supply:** To be hauled by contract company.
6. **Source of Construction Materials:**
All caliche required for construction of the drill pad and the proposed new access road will be obtained from a BLM approved caliche pit.
7. **Methods of Handling Waste Disposal:**
- A.** Drill cuttings not retained for evaluation purposes will be disposed of into the reserve pit.
- B.** Drilling fluids will be contained in steel mud tanks. The reserve pit will contain any excess drilling fluids or flow from the well during drilling, cementing, and completion operations. The reserve pit will be an earthen pit, approximately 60'X 90'X10' deep and fences on three sides prior to drilling. It will be fenced on on the fourth side immediately following rig removal. The reserve will be plastic-lined to minimize loss of drilling fluids and saturations of the ground with brine water.
- C.** Water produced from the well during completion may be disposed into the reserve pit or steel tank. After the well is permanently placed on production, produced water will be collected in tanks until hauled by transport to an approved disposal system or separate disposal application will be submitted for appropriate approval. Produced oil will be collected in steel tanks until sold.
- D.** A portable chemical toilet will be provided on the location for human waste during the drilling and completion operations.
- E.** Garbage and trash produced during drilling and completion will be put in trash trailer. If well is productive, maintenance waste will be placed in special trash cans and hauled away periodically. All waste material will be contained to prevent scattering by the wind. No toxic waste or hazardous chemicals will be produced by this operation.
- F.** After the rig is moved out and the well is either completed or abandoned, all waste materials will be cleaned-up within 30 days. No adverse materials will be left on the location. The reserve pit will be completely fenced and kept closed until it has dried. When the reserve pit is dry enough to break out and fill and, as weather permits, the unused portion of the well site will be leveled and re-seeded as per BLM specifications. Only the part of the pad required for production will be kept in use. In the event of a dry hole, only a dry hole marker will remain.
8. **Ancillary Facilities:**
No airstrip, campsite, or other facilities will be built as a result of the operations of this well.