Form 3160-5 (November 1994)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVEDOMB No. 1004-0135 Expires July 31, 1996

Date

SUNDR	BUREAU OF LAND MANAGEMENT Y NOTICES AND REPORTS ON WI	N.M. DIV Distas Perial No.
Do not use the abandoned we	nis form for proposals to drill or to re ell. Use Form 3160-3 (APD) for such p	ELLS 1301 W. Grand Avenue roposals. Artesia, NM ⁶ . 88210 Hottee or Tribe Name
SUBMIT IN TRIPLICATE - Other instructions on reverse side 1. Type of Well 2. Name of Operator BURNETT OIL CO., INC. 3a. Address BURNETT PLAZA SUITE 1500 1 CHERRY STREET UNIT #9 FORT WORTH TX 76102-6881 817/332-5108 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) UNIT A, 990' FNL, 330' FEL, SEC 24,T17S,R30E 7. If Unit or CA/Agreement, Name and/or No 8. Well Name and No. JACKSON A #20 9. API Well No. 30-015-31670 10. Field and Pool, or Exploratory Area CEDAR LAKE YESO 11. County or Parish, State Eddy County, N.M.		7 If Unit or CA/Agreement Name and/or No
		JACKSON A #20
		io. (include area code) 30-015-31670 31 817/332-5108 10. Field and Pool, or Exploratory Area
		12. CHECK AP
TYPE OF SUBMISSION		TYPE OF ACTION
Notice of Intent	Acidize Deepen Alter Casing Fracture To	
Subsequent Report Final Abandonment Notice	Casing Repair New Const Change Plans Plug and A Convert to Injection Plug Back	Abandon
If the proposal is to deepen dire Attach the Bond under which the following completion of the inv	ectionally or recomplete horizontally, give subsurfa- the work will be performed or provide the Bond Novolved operations. If the operation results in a mul- tinal Abandonment Notices shall be filed only after	luding estimated starting date of any proposed work and approximate duration thereof. ace locations and measured and true vertical depths of all pertinent markers and zones. Io. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days ltiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once at all requirements, including reclamation, have been completed, and the operator has
		487.78' w/notched Texas pattern shoe, w/float valve in
		ts thread locked. BJ pumped 400 sks Class "C"
cement w/2% CaCl. Bump plug 12:20PM. Cement dropped 76' after one hour, pumped 2 yards rat hole cement to bring back to surface. WOC 18 hrs(per NMOCD requirement.) No BLM for job.		
back to surface. WOC 1	o insper rances requirements	ACCEPTED FOR RECORD
		RECEIVED RECEIVED OCD ARTESIA PETROLEUM ENGINEER
14. I hereby certify that the foregoin Name (Printed/Typed)	ng is true and correct STERLING RANDOLPH	Title PETROLEUM ENGINEER
Signature /	1/1/1/1	Date Da To Da P 2 (2001

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Title

Office

Approved by