

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTSUBMIT IN TRIPLICATE*
(Other instructions on
reverse side)PLEASE EXPEDITE THIS APD.
DRILLING RIG PROMISED.FORM APPROVED
OMB NO. 1004-0136
Expires: February 28, 1995

APPLICATION FOR PERMIT TO DRILL OR DEEPEN

1a. TYPE OF WORK

DRILL ☒DEEPEN ☐

b. TYPE OF WELL

OIL
WELL ☐GAS
WELL ☒

OTHER

25111

SINGLE
ZONE ☒MULTIPLE
ZONE ☐

2. NAME OF OPERATOR

HUDSON OIL COMPANY OF TEXAS.

(RANDALL HUDSON 817-336-7109)

(JON SMITH 505-676-2266)

3. ADDRESS AND TELEPHONE NO.

616 TEXAS STREET

FORT WORTH, TEXAS 76102

817-336-7109

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)*

At surface

1680' FNL & 1780' FEL SEC. 13 T17S-R31E EDDY CO. NM

At proposed prod. zone SAME

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*

Approximately 4 miles West of Maljamar New Mexico.

15. DISTANCE FROM PROPOSED*

LOCATION TO NEAREST
PROPERTY OR LEASE LINE, FT.
(Also to nearest drlg. unit line, if any)

1680'

16. NO. OF ACRES IN LEASE

1120±

17. NO. OF ACRES ASSIGNED
TO THIS WELL

320

18. DISTANCE FROM PROPOSED LOCATION*

TO NEAREST WELL, DRILLING, COMPLETED,
OR APPLIED FOR, ON THIS LEASE, FT.

2600'±

19. PROPOSED DEPTH

14,600'

20. ROTARY OR CABLE TOOLS

ROTARY

21. ELEVATIONS (Show whether DF, RT, GR, etc.)

3941' GR.

22. APPROX. DATE WORK WILL START*

WHEN APPROVED

23.

PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	GRADE SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
25"	Conductor	NA	40'	Cement to surface with Redi-mix.
17½"	K-55 13 3/8"	54.5	650'	700 Sx. circulate cement to sur.
12½"	L-80 9 5/8"	40	4600'	1550 Sx. " " " "
8 3/4"	L-80 7"	29	14,600'	2015 Sx. Estimate TC 1600'.

1. Drill 25" hole to 40'. Set 40' of 20" conductor and cement to surface with Redi-mix.
2. Drill 17½" hole to 650'. Run and set 650' of 13 3/8" 54.5# J-55 ST&C casing. Cement with 700 Sx. of Class "C" cement + 2% CaCl + ¼# Flocele/Sx. , circulate cement to surface.
3. Drill 12½" hole to 4600'. Run and set 4600' of 9 5/8" 40# L-80 ST&C casing. Cement with 1550 Sx. of Class "C" cement + 2% CaCl + ¼# Flocele/Sx. , circulate cement to surface.
4. Drill 8 3/4" hole to 14,600'. Run and set 14,600' of 7" 29# L-80 LT&C casing. Cement with 2015 Sx. of Class "H" Premium Plus cement + additives. Estimate top of cement 1600' from surface.

Roswell Controlled Water Basin

APPROVAL SUBJECT TO
GENERAL REQUIREMENTS AND
SPECIAL STIPULATIONS
ATTACHED

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24.

SIGNED

Joe T. Janice

TITLE

RECEIVED
OCD ARTESIA

DATE 08/20/01

(This space for Federal or State office use)

PERMIT NO.

APPROVAL DATE

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY

/S/ JOE G. LARA

TITLE

FIELD MANAGER

DATE

SEP 27 2001

*See Instructions On Reverse Side

APPROVAL FOR 1 YEAR

BUREAU OF LAND MGMT
ROSWELL OFFICE

2001 AUG 21 AM 8:43

RECEIVED

121 700 2 11 14