

AMENDED FOR MOVE OF 50' FSL AT REQUEST OF BARRY HUNT. 1750' TO 1800'

DRILLING PLAN

BURNETT OIL CO., INC.
LEASE NO.NMLC 029338A
GISSLER A LEASE, WELL NO.17
UNIT LETTER K
1800' FSL, 2310' FWL
SECTION 14, TOWNSHIP 17 SOUTH, RANGE 30 EAST
EDDY COUNTY, NEW MEXICO

(A) DRILLING PROGRAM

(1) Estimated tops of geologic markers:

Alluvium.....Surface
Anhydrite.....233'
Salt.....475'
Base Salt.....1130'
Yates.....1314'
Seven Rivers.....1590'
Grayburg.....2604'
San Andres.....2940'
Glorieta.....4500'

(2) Estimated depths of producing formations:

Fresh water.....None
Saltwater flows..(?)*
Oil and Gas.....1590'**,2604**

* As waterflows, if any, are encountered, their depth will be recorded, and drilling will continue to total depth. Multiple stage cementers will be placed in the production casing string to enable us to confine the waterflows to their respective depths by cementing.

** Oil and gas bearing zones, if any, will be determined by log analysis, and will be confined by cementing; subsequently perforated, stimulated and produced in a conventional manner.

(3) Blowout Preventer Specifications:

A 3000 PSI Double Ram unit with hydraulic closing equipment. (See Exhibit E schematic). The preventer will be tested before drilling out below surface pipe setting depth. The exact description of the preventer and related equipment will depend on the successful contractor, who has not yet been selected. No high pressure hydrocarbon zones are anticipated.

(4) Supplementary drilling equipment information:

Not available at this time.