## DIL JUNSERVATION COMMIT ION

Santa Fe, New Mexico

COPY

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

## Indicate nature of report by checking below:

	31	
REPORT ON BEGINNING DRILLING OPERA-	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEM- ICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	NOTICE OF INTENTION TO PLUG WELL	X.
	Artesia, New Mexico 6-11-44	
OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO. Gentlemen:	Place Date	
Following is a report on the work done and the results of Malco Refineries, Inc. Kelly-Miller	obtained under the heading noted above at the	
Company or Operator	Well No. 2 in	n the
of Sec2	, т. <u>18S</u> , к. <u>25Е</u> , N. м. Р	M
Wildest Field,	Eddy Co	intv.
	itted on Form C-102 on 19	
DETAILED ACCOUNT OF WO Plug back and set a 5 sax cement pl 2073-84. Then plug back and set a 5 sa Will allow this cement to come up into	7". Will knock off 7" and pull. Will	Om
DETAILED ACCOUNT OF WO Plug backend set a 5 sax cement pl 2073-84. Then plug back and set a 5 sa Will allow this cement to come up into then pull 5" at 906 fill with mud and sartesian water @ 505'. Put regulation	ORK DONE AND RESULTS OBTAINED ag above 2070. This will shut off HFW from cement plug at bottom of 7" @ 1175. 7". Will knock off 7" and pull. Will spot cement plug immediate above top	Off (1
DETAILED ACCOUNT OF WO Plug backend set a 5 sax cement pl 2073-84. Then plug back and set a 5 sa Will allow this cement to come up into then pull 6" at 906 fill with mud and sartesian water @ 565'. Put regulation	ORK DONE AND RESULTS OBTAINED ag above 2070. This will shut off HFW from cement plug at bottom of 7" @ 1175. 7". Will knock off 7" and pull. Will spot cement plug immediate above top	OHA.
DETAILED ACCOUNT OF WO Plug backend set a 5 sax cement pl 2073-84. Then plug back and set a 5 sa Will allow this cement to come up into then pull 5" at 906 fill with mud and sartesian water @ 565'. Put regulation	ORK DONE AND RESULTS OBTAINED aug above 2070. This will shut off HFW from cement plug at bottom of 7" @ 1175. 7". Will knock off 7" and pull. Will spot cement plug immediate above top plug and marker in op of hole.	
DETAILED ACCOUNT OF WO Plug backend set a 5 sax cement plug back and set a 5 sax will allow this cement to come up into then pull 5" at 906 fill with mud and sartesian water @ 505'. Put regulation  Witnessed by	Company  Com	
DETAILED ACCOUNT OF WO Plug backend set a 5 sax cement plug back and set a 5 sax will allow this cement to come up into then pull 5" at 906 fill with mud and sartesian water @ 505'. Put regulation  Witnessed by	Company  Title  Company  Company  Company  Title  Company  Title  Company	
DETAILED ACCOUNT OF WO Plug backend set a 5 sax cement plug back and set a 5 sax will allow this cement to come up into then pull 5" at 906 fill with mud and sartesian water @ 505'. Put regulation  Witnessed by	Company  Company  Company  Company  Title  Company  Company  MALCO REFINERIES, INC.	
DETAILED ACCOUNT OF WO Plug backend set a 5 sax cement plug back and set a 5 sax will allow this cement to come up into then pull 5" at 906 fill with mud and sartesian water @ 505'. Put regulation  Witnessed by	Company  Title  Company  Company  Company  Title  Company  Title  Company	
DETAILED ACCOUNT OF WO Plug backend set a 5 sax cement pl 2073-84. Then plug back and set a 5 sa Will allow this cement to come up into then pull 5" at 906 fill with mud and s artesian water @ 505'. Put regulation  Witnessed by  Name  Subscribed and sworn before me this  day of	Company  Company  Company  Company  Company  Company  Title  Company  Company  Company  Company  Company  Title  Company  Company  Company  Company  Company  Title  Company  Company  Company  Title  Company  Company  Company  Title  Company  Company  Company  Title	
DETAILED ACCOUNT OF WO Plug backend set a 5 sax cement pl 2073-84. Then plug back and set a 5 sa Will allow this cement to come up into then pull 6" at 906 fill with mud and s artesian water @ 505'. Put regulation  Witnessed by  Name  Subscribed and sworn before me this  day of	Company  Company  Company  Company  Company  Title  Company  Company  Title  Company  Company  Company  Title  Company  Company  Company  Title  Company  Company  Title  Company  Title  Company  Company  Title  Company	
DETAILED ACCOUNT OF WO Plug backend set a 5 sax cement pl 2073-84. Then plug back and set a 5 sa Will allow this cement to come up into then pull 5" at 906 fill with mud and s artesian water @ 505'. Put regulation  Witnessed by  Name  Subscribed and sworn before me this  day of	Company  Company  Company  Company  Company  Title  Company  Company  Title  Company  Company  Company  Title  Company  Company  Title  Company  Company  Title  Company  Title  Company  Company  Title  Company  Company  Title  Company  Company  Company  Company  Company  Title  Company  Com	