

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	RECEIVED MAR 23 1964 O. C. C. ARTESIA, OFFICE
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

March 20, 1964
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Gulf Oil Corporation Eddy State "AC" ✓ Well No. 1 in L
(Company or Operator) (Unit)
NW 1/4 SW 1/4 of Sec. 36, T. 18-S, R. 25-E, NMPM, Wilcat Pool
(40-acre Subdivision)
Eddy County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

9283' TD, 9218' PB. It is proposed to plug and abandon as follows:

1. Set GI BP at approximately 8950' and spot 5 sacks cement on top.
2. Run free point indicator and cut 5-1/2" casing off immediately above free point with jet cutter and pull casing.
3. Spot cement plug from 8050 to 7950 - across casing cut, 6900' to 6800' - across Permo-Penn, 5750' to 5650' - across W. C. Grab, 4500' to 4400' - across top Abe, 2200' to 2100' - across Glorietta, 1250' to 1150' - across surface casing shoe and 50' to surface. If the casing is recovered from a shallower depth a 100' cement plug will be set across the cut with 50' inside casing and 50' in open hole, and plugs to surface.
4. Install 4" X 4' dry hole marker and clean location.

Approved..... MAR 23 1964 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

Gulf Oil Corporation

ORIGINAL Copy of Operator

By..... C. D. BORLAND

Position..... Area Production Manager

Send Communications regarding well to:

Name..... Gulf Oil Corporation

Address..... Box 670, Hobbs, New Mexico

OIL CONSERVATION COMMISSION

ARTESIA DISTRICT OFFICE

No. Copies Received

4

DISTRIBUTION

	NO FORWARDED	
OPERATOR	2	
SANTA FE	1	
PRODUCTION OFFICE		
STATE LAND OFFICE		
U. S. G. S.		
TRANSPORTER		
FILE	1	
BUREAU OF MINES		