

N

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

|  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |

AREA 640 ACRES  
LOCATE WELL CORRECTLY

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

Suppes &amp; Suppes

Tulsa, Oklahoma

Company or Operator

Address

Rogers

Well No.

1

in SE SW NE of Sec.

10

T. 18

Lease

R. 26

N. M. P. M.

Dayton

Field,

Eddy

County.

Well is 2310 feet south of the North line and 1650 feet west of the East line of Sec. 10-18-26

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Charles Rogers Address Artesia, New Mexico

If Government land the permittee is Address

The Lessee is Suppes &amp; Suppes Address Tulsa, Oklahoma

Drilling commenced Nov. 26 1940 Drilling was completed January 21 1941

Name of drilling contractor Suppes &amp; Suppes Address Tulsa, Oklahoma

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until 19

## OIL SANDS OR ZONES

No. 1, from 815' to 843 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 965 to 975 feet. Top of hole

No. 2, from 1057 to 1058 feet. Flowing

No. 3, from to feet.

No. 4, from to feet.

## CASING RECORD

| SIZE  | WEIGHT PER FOOT | THREADS PER INCH | MAKE | AMOUNT | KIND OF SHOE | CUT & FILLED FROM | PERFORATED |    | PURPOSE |
|-------|-----------------|------------------|------|--------|--------------|-------------------|------------|----|---------|
|       |                 |                  |      |        |              |                   | FROM       | TO |         |
| 8 1/4 | 28              | 8                | used | 682    | Texas        |                   |            |    |         |
| 7     | 24              | 10               | used | 815    | Halliburton  |                   |            |    |         |
|       |                 |                  |      |        |              |                   |            |    |         |
|       |                 |                  |      |        |              |                   |            |    |         |
|       |                 |                  |      |        |              |                   |            |    |         |
|       |                 |                  |      |        |              |                   |            |    |         |
|       |                 |                  |      |        |              |                   |            |    |         |

## MUDDING AND CEMENTING RECORD

| SIZE OF HOLE | SIZE OF CASING | WHERE SET | NO. SACKS OF CEMENT | METHOD USED | MUD GRAVITY | AMOUNT OF MUD USED |
|--------------|----------------|-----------|---------------------|-------------|-------------|--------------------|
| 11           | 8 1/4          | 682       | 20                  | Halliburton |             | 100 sacks          |
| 7 7/8        | 7              | 815       |                     |             |             | Circulated mud     |

## PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

| SIZE | SHELL USED | EXPLOSIVE OR CHEMICAL USED | QUANTITY | DATE | DEPTH SHOT OR TREATED | DEPTH CLEANED OUT |
|------|------------|----------------------------|----------|------|-----------------------|-------------------|
|      |            |                            |          |      |                       |                   |
|      |            |                            |          |      |                       |                   |
|      |            |                            |          |      |                       |                   |

Results of shooting or chemical treatment

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from Surface feet to 815 feet, and from feet to feet

Cable tools were used from 815 feet to 1134 feet, and from feet to feet

## PRODUCTION

Put to producing 19

The production of the first 24 hours was barrels of fluid of which % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

## EMPLOYEES

Walter Herkimer

Driller

M. R. Stephens

Driller

A. J. Smith

Driller

W. C. Davis

Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 25th

day of Jan 1941

Calvin P. Dunn  
Notary Public

Artesia, New Mexico January 24, '41

Place

Date

Name B. L. Kennedy

Position Drilling Superintendent

Representing Suppes &amp; Suppes

Company or Operator

Address Tulsa, Oklahoma

My Commission expires MY COMMISSION EXPIRES OCT. 26 1941

# FORMATION RECORD

| FROM | TO   | THICKNESS<br>IN FEET | FORMATION            |
|------|------|----------------------|----------------------|
| 0    | 25   | 25                   | Clay                 |
| 25   | 35   | 10                   | Sand                 |
| 35   | 45   | 10                   | Anhydrite            |
| 45   | 90   | 45                   | Red Rock             |
| 90   | 360  | 270                  | Anhydrite            |
| 360  | 372  | 12                   | Lime                 |
| 372  | 390  | 18                   | Anhydrite broken     |
| 390  | 565  | 175                  | Anhydrite            |
| 565  | 670  | 105                  | Anhydrite & Red Rock |
| 670  | 695  | 25                   | Lime gray            |
| 695  | 720  | 25                   | Red sandy lime       |
| 720  | 815  | 95                   | Lime gray Hard       |
| 815  | 843  | 28                   | Sand                 |
| 843  | 895  | 52                   | Gray lime Hard       |
| 895  | 930  | 35                   | Gray lime            |
| 930  | 935  | 5                    | Sandy lime           |
| 935  | 965  | 30                   | Sand brown           |
| 965  | 975  | 10                   | Sand                 |
| 975  | 1046 | 71                   | Lime gray            |
| 1046 | 1051 | 5                    | Sandy lime           |
| 1051 | 1057 | 6                    | Lime gray            |
| 1057 | 1058 | 1                    | Sand                 |
| 1058 | 1134 | 76                   | Gray lime            |