

30-015-00215

Rec'd. 5-16-66
1-Multi-Point Back Pressure
Test

Ogrod-25575

P.O.P. - 12176

pool - 96113

4-30-91

TRACER SURVEY

8700 - 8993

IT IS THEREFORE ORDERED: SWD R-7600 7/23/84

(1) That the applicant, Yates Petroleum Corporation, is hereby authorized to utilize its Dayton Townsite Well No. 1, located ¹²⁵⁰~~1980~~ feet from the North line and ²³¹⁰~~1980~~ feet from the East line of Section 21, Township 18 South, Range 26 East, NMPM, Eddy County, New Mexico, to dispose of produced salt water into the Morrow formation, injection to be accomplished through 2 7/8-inch tubing installed in a packer set at approximately 8853 feet, with injection into the perforated interval from approximately 8,901 to 9,062 feet.

4-22-88
Injectivity profile
Temperature
8700-9087
1-18-89
Injectivity Profile
Temperature
8700'-9079'

9-20-84

INJECTIVITY
PROFILE TEMP

8750 - 9090

9-24-86
Inj. Profile Temp -
8750 - 9084

SWD R-7600

NC TORS PER LLA

PENN- 7120

STRAWN- 8070

ATDKA - 8399

MOR. LS - 8810

MOR. CI - 8860

CHES. - 9142

qlo. - 2237

gso - 2470

improvement installed 10/1/72

6-5558