

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	X	REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

Place

Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Valley Refining Company Hoffman Well No. 2 in the
Company or Operator Lease

S.E. 14 of Sec. 24, T. 18S, R. 26E, N. M. P. M.,
Dayton Field, Eddy County.

The dates of this work were as follows: May 21, 1945 thru May 24, 1945Notice of intention to do the work was (was not) submitted on Form C-102 on October 16 1945

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

As outlined on Form C-102 dated October 16th. The well was plugged back to 1208 from a T.D. of 2899. Bottom waters shut off completely. We then shot with 50 quarts of Nitro from 1140 to 1158 with no results. We then plugged back to 1190 and shot with 240 quarts of Solidified from 1040-1090. An umbrella was used with 5 sac calumet and 35' of gravel. No results from shot. The well was filled with aquaplug and set wooden plug capped with 5 sac of cement. The 9'5" of 7" O.D. Csg. was left in well, with 1 x 2" sledge and 2" gate valve left on top. Pits burned, drained and leveled.

Witnessed by Bill Hudson Indep. Op.
Name Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

day of , 19

Name

Position

Notary Public

Representing

Company or Operator

My commission expires

Address

Remarks:

Approved 11-16-45

Name

Title

