<u>990 5</u>	2623/E (Perm C-262) (Revised 7/1/88)
--------------	--

NUMBER OF COPI	ES RECEI	1ED 1	
0	STRIBUTI	DN C	
SANTA FE			
FILE		1-	NE
U.S.G.S.			
LAND OFFICE		<b> </b>	
TRANSPORTER	OIL		
	GAS		[
PRORATION OFFI	CE		
OPERATOR			

### W MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

# MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

### Indicate Nature of Notice by Checking Below

Notice of Intention to Change Plans	x	Notice of Intention to Temporarily Abandon Well	Notice of Intention to Drill Deeper	
NOTICE OF INTENTION TO PLUG WELL		Notice of Intention to Plug Back	Notice of Intention to Set Liner	
Notice of Intention to Squeeze		Notice of Intention to Acidize	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE (OTHER)		Notice of Intention (Other)		

OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

(Place)

Odessa, Texas June 23, 1964 (Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the. Kewanee Oil Company

····	Williams		В
(Company or Operator)	Lease		(Unit)
NW 1/4 NE 1/4 of Sec. 25 T. 1	S R 26E NMPM	Dayton Grayburg	Pool
(40-acre Subdivision)		······································	FOU

Eddy......County.

### FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Set Lynes packer at 930 feet. Tested 7" casing. Casing loses fluid at rate of 1/4 barrel per minute at 1400 psi.

Propose to plug back with sand and Calseal to top of pay at 1063 feet. Set 4-1/2" OD casing at 1050 feet and cement to surface with regular cement. Drill out under 4-1/2" casing and test casing to 1500 psi. Drill out plug to original total depth of 1075 feet. Set Baker Model A tension packer immediately above casing shoe on fiber glass tubing and start water injection.

## RECEIVED

JUN 2 5 1964

Approved	D. C. C. ARTEBIA, OFFICE Kewanee Oil Company	
Except as follows:	By	
Approved OIL CONSERVATION COMMISSION	Send Communications regarding well to:	
By h. G. Aressett	Name. Kewanee Oil Company	
Title	Address. P. O. Box 3786, Odessa, Texas	