



NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

R. D. Collier (Company or Operator) Scripps (Land)
Well No. 2, in NE 1/4 of NW 1/4, of Sec. 25, T. 18-S, R. 26-E, NMPM.
Dayton Pool, Eddy County.
Well is 2310 feet from South line and 1650 feet from West line
of Section 25. If State Land the Oil and Gas Lease No. is
Drilling Commenced 10-20, 1956. Drilling was Completed 12-27, 1956
Name of Drilling Contractor Haynes Drilling Co.
Address Artesia, N. Mex.
Elevation above sea level at Top of Tubing Head. The information given is to be kept confidential until
19

OIL SANDS OR ZONES

No. 1, from 1035 to 1040 No. 4, from to
No. 2, from 1070 to 1076 No. 5, from to
No. 3, from 1170 to 1174 No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 40 to 60 feet.
No. 2, from 140 to 160 feet.
No. 3, from 750 to 790 feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8	28	used	330	Texas Pattern			circulated
5-1/2	15	"	1005	regular			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8-5/8	330	50	circulated		
7-7/8"	5-1/2	1005	100	cemented		cemented w/100 sacks

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Treated open 1005' to 1200' - 6000 lbs & 6000 gal. lease crude
350 bbls. oil and sand
Result of Production Stimulation good
Depth Cleaned Out

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

Rotary tools were used from.....feet to.....feet, and from.....feet to.....feet.
Cable tools were used from.....0.....feet to.....1881.....feet, and from.....feet to.....feet.

Put to Producing.....**12-27**....., 19**56**

GAS WELL: The production during the first 24 hours was.....M.C.F. plus.....barrels of liquid Hydrocarbon. Shut in Pressure.....lbs.

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

T. Anhy.....	T. Devonian.....	T. Ojo Alamo.....
T. Salt.....	T. Silurian.....	T. Kirtland-Fruitland.....
B. Salt.....	T. Montoya.....	T. Farmington.....
T. Yates.....	T. Simpson.....	T. Pictured Cliffs.....
T. 7 Rivers.....	T. McKee.....	T. Menefee.....
T. Queen.....450	T. Ellenburger.....	T. Point Lookout.....
T. Grayburg.....923	T. Gr. Wash.....	T. Mancos.....
T. San Andres.....1197	T. Granite.....	T. Dakota.....
T. Glorieta.....	T.	T. Morrison.....
T. Drinkard.....	T.	T. Penn.....
T. Tubbs.....	T.	T.
T. Abo.....	T.	T.
T. Penn.....	T.	T.
T. Miss.....	T.	T.

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	923	923	Shale, sand, Anhy.				
923	1197	274	Lime & sand				
1197	1881	684	Lime				

March 25, 1959 (Date)

Company or Operator..... R. D. Collier..... Address..... Box 798, Artesia, N. Mex.

Name..... Position or Title..... Owner