


N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD



HOBBS OFFICE

AREA 640 ACRES
LOCATE WELL CORRECTLY

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

Brewer Drilling Co. Etal **Artesia, New Mexico**
 Company or Operator Address
O. M. Kindle Well No. **1** in SW $\frac{1}{4}$ - NE $\frac{1}{4}$ of Sec. **26**, T. **18**
 Lease
 R. **26** N. M. P. M., **Dayton** Field, **Eddy** County.
 Well is **2310** feet south of the North line and **2310** feet west of the East line of **Sec 26**
 If State land the oil and gas lease is No. _____ Assignment No. _____
 If patented land the owner is **O. M. Kindle Etal** Address **Virden, Ill.**
 If Government land the permittee is _____ Address _____
 The Lessee is **Brewer Drilling Co. Etal** Address **Artesia, New Mexico**
 Drilling commenced **11-25** 19____ Drilling was completed **12-21** 19**40**
 Name of drilling contractor **Brewer Drilling Co.** Address **Artesia, New Mexico**
 Elevation above sea level at top of casing _____ feet.
 The information given is to be kept confidential until _____ 19____.

OIL SANDS OR ZONES

No. 1, from **985** to **995 - Gas** No. 4, from _____ to _____
 No. 2, from _____ to _____ No. 5, from _____ to _____
 No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from **45** to **55** feet. **H P W**
 No. 2, from **790** to **795** feet. **Flowing**
 No. 3, from **805** to **820** feet. **Artesian**
 No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
10	40	8	Wheeling	192	Reg	Mudded			Water
8 1/4	32	8	"	843	"	"			"
7"	20	8	"	902	"	"			"

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12 1/2	10	192	none	none	none	Swung
10	8 1/4	743	200	Halliburton	Heavy	220
8 1/4	7	902	140	"	"	200

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
 Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
6 5/8	5"	Nitro Glycerin	40 Qts	12-21-40	985-995	1001

Results of shooting or chemical treatment **Increased gas - Strictly a gas well.**

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet
 Cable tools were used from **0** feet to **1193** feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing **No. oil** 19____
 The production of the first 24 hours was _____ barrels of fluid of which _____ % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, Be _____
 If gas well, cu. ft. per 24 hours **1 1/2 million** Gallons gasoline per 1,000 cu. ft. of gas **none**
 Rock pressure, lbs. per sq. in. _____

EMPLOYEES

Carl Byler Driller **C. V. Miller** Driller
B. R. Polk Driller **J. B. Bryant** Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this **30th** **Artesia, New Mexico** **Dec. 30, 1940**
 day of **December** 19 **40** Name **C. V. Miller**
Carl Byler Notary Public Position **Partner**
 My Commission expires **Sept. 25, 1944** Representing **Brewer Drilling Co. Etal**
 Company or Operator Address **Box 566, Artesia, New Mexico**

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	95	95	Caleche
95	335	240	Red rock & Gravel
335	400	65	Red rock and anhydrite
400	565	165	Anhydrite
565	595	30	Red Shale
595	730	135	Anhydrite
730	795	65	Red Shale
795	820	25	Red Sand & Shells
820	835	15	Broken Lime
835	843	8	Hard Gray line- set 8 1/2 csg.
843	855	12	Sandy Lime - Some water
855	902	47	Brown Lime - Set 7" csg.
902	1193	291	Brown & gray lime
1193			Total depth of Hole
Plugged back to 995 - shot from 985 to 995 for gas.			