FORM C-105

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Brewer Drilling Company   Box 566, Artesia, New Mexico
Company or Operator   _Address_

Kindle   Well No. 2   in NE NE of Sec. 26   T. 18
Lease

R. 26   N. M. P. M.   Dayton   Field,   Eddy   County.

Well is 330 feet south of the North line and 330 feet west of the East line of Sec. 26-18-26

If State land the oil and gas lease is No.   Assignment No.

If patented land the owner is O. L. Kindle   Address Virdin, Illinois

If Government land the permittee is   Address

The Lessee is   Address

Drilling commenced August 12, 19 43. Drilling was completed October 25, 19 43

Name of drilling contractor Myron Bruning   Address Artesia, New Mexico

Elevation above sea level at top of casing   feet.

The information given is to be kept confidential until   19

OIL SANDS OR ZONES

No. 1, from 985 to 995   No. 4, from   to

No. 2, from   to   No. 5, from   to

No. 3, from   to   No. 6, from   to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 20 to 750   feet.

No. 2, from   to   feet.

No. 3, from   to   feet.

No. 4, from   to   feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM	PERFORATED TO	PURPOSE
7"	20-lb	8-thrd	New	920	Texas-St				Wtr String & Oil String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
8 5/8	7"	920	200	Halliburton	Hole Full Aquagel	

PLUGS AND ADAPTERS

Heaving plug—Material   Length   Depth Set

Adapters—Material   Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
70 qts	4 3/4"	Nitro Glycerin	70 qts	10-27-43	982-1012	1040

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 920 feet, and from   feet to   feet

Cable tools were used from 920 feet to 1045 feet, and from   feet to   feet

PRODUCTION

Put to producing   19

The production of the first 24 hours was 8 barrels of fluid of which 100 % was oil;   %

emulsion;   % water; and   % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours   Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

Myron Bruning   Driller   C. S. Powell   Driller

Clay Cade   Driller   Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 1st   Artesia, New Mexico   November 1, 1943
                                                              Place   _Date_

day of November 1943   Name _C. S. Brewer_

Notary Public   Position Partner

My Commission expires My Commission Expires March   Representing Brewer Drilling Company
                                                                                        Company or Operator

Address Box 566, Artesia, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	860	860	Red Rock, Sand and Gyp
860	865	5	Red Rock
865	985	120	Lime
985	995	10	Sand - Oil sand
995	1045	50	Lime
1045			TOTAL DEPTH