

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

PLUGGING
FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>NATIONAL DRILLING CO.</u>		Lease <u>KINDLE</u>		Well # <u>2</u>	
Location of Well	Unit <u>NENE</u>	Section <u>26</u>	Township <u>18^S</u>	Range <u>26^E</u>	County <u>EDDY</u>
<u>PLUGGING</u> Drilling Contractor	<u>Davis well service</u>		Type of Equipment <u>pulling unit</u>		
<u>APPROVED CASING PROGRAM</u> <u>IN HOLE</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
	<u>7"</u>	<u>20[#]</u>	<u>NEW</u>	<u>920'</u>	<u>100 scks.</u>

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole _____ Size of Casing _____ Sacks cement required _____

Type of Shoe used _____ Float collar used _____ Btm 3 jts welded _____

TD of hole 1045 Set _____ Feet of _____ Inch _____ # Grade _____

New-used csg. @ _____ with _____ sacks neat cement around shoe

+ _____ sax _____ additives _____

Plug down @ _____ (AM) (PM) Date _____

Cement circulated _____ No. of Sacks _____

Cemented ~~by~~ plug by HALLIBURTON Witnessed by LOBLEY

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: well to be plugged as follows:
Hole to be loaded with mud between plugs.
1. 2.5 scks. at T.D. 1045'
2. 2.0 scks. at 900'
3. 2.0 scks. at 450'

Marker is at and C-10? can be signed when we get it.

