

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-015-00252
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Hawkins GY
8. Well No.	4
9. Pool name or Wildcat	Atoka Penn
10. Elevation (Show whether OF, RKR, RT, GR, etc.)	3338' KB

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter C : 990 Feet From The North Line and 650 Feet From The West Line Section 27 Township 18S Range 26E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Frac Morrow perfs <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-19-21-98 - Unset packer. Pulled up and reset packer at 8911'. Removed BOP and nipped up wellhead. Swabbed tubing down to 7500'. Rigged up slickline. Pulled standing valve out of packer at 8911'. Rigged down slickline. Pressure tested annulus to 2000 psi. Swabbed tubing dry. Shut well in.

9-22-98 - Installed treesaver. Frac'd perforations 9002-9074' with 30000 gallons 70Q foam, 25000# 20-40 AC-frac proppant and 91 tons CO2 - screened out. Removed treesaver. Opened well to flow back frac.

9-23-98 - Flowed and swabbed back frac. Shut well in.

9-24-98 - Flared well down to pit. Swab and flow tested. Shut well in.

9-25-98 - Flared well to pit. Flow tested. Shut well in.

9-26-28-98 - Flared well down to pit. Flow tested. Shut well in.

9-29-98 - Flared well down to pit. Rigged up wireline. TIH and set standing valve in packer at 8878'. Rigged down wireline. Loaded tubing with 2% KCL water. Nipped down wellhead. Installed BOP. Get off on/off tool and TOOH. Laid down L-80 tubing.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Oct. 1, 1998

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR


APPROVED BY _____ TITLE _____ DATE 10-8-98

CONDITIONS OF APPROVAL, IF ANY:

YATES PETROLEUM CORPORATION
Hawkins GY #4
Section 27-T18S-R26E
Eddy County, New Mexico

SUNDRY NOTICE CONTINUED:

TIH with 2-7/8" J-55 tubing. Reversed hole clean. Get on on/off tool. Removed BOP. Nippled up wellhead. Swabbed tubing down to 4000'. Rigged up wireline. Pulled standing valve. Rigged down wireline. Flow and swab. Shut well in. 9-30-98 - Flared well down to pit. Rigged up wireline. TIH with logging tools and ran after-frac log. NOTE: Casing had sand fill. Got logging tools down to 9031', 40' above bottom perforations. TOOH with logging tools and rigged down wireline. Flared well to pit. Shut well in. Released well to production department.



Rusty Klein
Operations Technician
October 1, 1998

Note: All perfs 9002-9074' (Morrow) open
