

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

OCT 2 1959

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

E. P. Campbell

Cleveland

(Company or Operator)

(Lease)

Well No. 1, in NW 1/4 of NE 1/4, of Sec. 33, T. 18 South, R. 28 East, NMPM.
Wildest Pool, 1880 County.

Well is 660 feet from North line and 1980 feet from East line

of Section 33. If State Land the Oil and Gas Lease No. is

Drilling Commenced November 12, 1958, 19 Drilling was Completed September 15, 59

Name of Drilling Contractor E. P. Campbell

Address 1603 Broadway, Lubbock, Texas

Elevation above sea level at Top of Tubing Head 3376. The information given is to be kept confidential until Not confidential, 19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 800 to 850 feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

| SIZE | WEIGHT PER FOOT | NEW OR USED | AMOUNT | KIND OF SHOE | CUT AND PULLED FROM | PERFORATIONS | PURPOSE |
|---------|-----------------|-------------|--------|--------------|---------------------|--------------------------------|-------------------|
| 12-1/2" | 24 | New | 1100 | Halliburton | guide shoe | | Surface string |
| 12-1/2" | 14 | New | 6107 | " | " | See Attached sheet for perfor. | Production string |
| | | | | | | | |

MUDDING AND CEMENTING RECORD

| SIZE OF HOLE | SIZE OF CASING | WHERE SET | NO. SACKS OF CEMENT | METHOD USED | MUD GRAVITY | AMOUNT OF MUD USED |
|--------------|----------------|-----------|---------------------|-------------|-------------|--------------------|
| 12-1/2" | 8-5/8 | 1100 | 500 | Pump & Plug | | |
| 7-7/8" | 5-1/2 | 6107 | 1250 | Pump & Plug | | |
| | | | | | | |

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

See Attached Sheet

Result of Production Stimulation

Depth Cleaned Out 1056'

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 6107 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PLANNED & ABANDONED 9-15-59

PRODUCTION

Put to Producing, 19

OIL WELL: The production during the first 24 hours was barrels of liquid of which % was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity.

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

| | | |
|---|----------------|-----------------------|
| T. Anhy | T. Devonian | T. Ojo Alamo |
| T. Salt | T. Silurian | T. Kirtland-Fruitland |
| B. Salt | T. Montoya | T. Farmington |
| T. Yates | T. Simpson | T. Pictured Cliffs |
| T. 7 Rivers | T. McKee | T. Menefee |
| T. Queen | T. Ellenburger | T. Point Lookout |
| T. Grayburg | T. Gr. Wash. | T. Mancos |
| T. San Andres | T. Granite | T. Dakota |
| T. Glorieta 2470' | T. | T. Morrison |
| T. Drinkard | T. | T. Penn. |
| T. 1111 1111 Spring 3980' | T. | |
| T. Abo 1800' | T. | |
| T. 1111 1111 5910' | T. | |
| T. Miss | T. | |

FORMATION RECORD

| From | To | Thickness in Feet | Formation | From | To | Thickness in Feet | Formation |
|---|-------|-------------------|------------------|------|----|-------------------|-----------|
| 0 | 1000' | 1000' | Sand & gravel | | | | |
| 1000 | 2470' | 1470' | Dolomite | | | | |
| 2470 | 3000' | 530' | Sand & dolomite | | | | |
| 3000 | 3980' | 980' | Dolomite & chert | | | | |
| 3980 | 4800' | 820' | Black limestone | | | | |
| 4800 | 5910' | 1110' | Dolomite | | | | |
| 5910 | 6107' | 197' | Limestone | | | | |
| The following plugs were used: 4750-4850 feet with 13 sacks cement 1050-1125 feet with 10 sacks cement Surface with 5 sacks cement. 4" marker at surface | | | | | | | |

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator E. F. Campbell

October 1, 1959 (Date)
Address 1603 Broadway, Lubbock, Texas

Name Guy J. Lundy

Position Title Geologist