

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

PLUGGING
FIELD REPORT FOR ~~CEMENTING~~ ~~SE~~ WELLS

| | | | | | |
|--|---------------------------------------|----------------------------|--|-----------------------------|--------------------|
| Operator <i>E.P. CAMPBELL</i> | | Lease <i>E.P. CAMPBELL</i> | | Well # <i>I-A</i> | |
| Location of Well | Unit <i>MEAN C</i> | Section <i>35</i> | Township <i>18^S</i> | Range <i>26^E</i> | County <i>EDDY</i> |
| PLUGGING Cementing Contractor | <i>HOBBS PIPE & SUPPLY CO.</i> | | Type of Equipment <i>PULLING UNIT.</i> | | |
| APPROVED CASING PROGRAM <i>IN HOLE.</i> | | | | | |
| Size of Hole | Size of Casing | Weight Per Foot | New or Used | Depth | Sacks Cement |
| | <i>8 5/8"</i> | <i>24#</i> | <i>NEW</i> | <i>900'</i> | <i>CIRCULATED</i> |
| | <i>5 1/2"</i> | <i>14#</i> | <i>NEW</i> | <i>5679</i> | <i>200 sks.</i> |
| | <i>5 1/2" Cut + pulled from 3878'</i> | | | | |
| Casing Data: | | | | | |
| Surface _____ joints of _____ inch _____ # Grade _____ | | | | | |
| (Approved) (Rejected) | | | | | |
| Inspected by _____ date _____ | | | | | |
| Cementing Program | | | | | |
| Size of hole _____ Size of Casing _____ Sacks cement required _____ | | | | | |
| Type of Shoe used _____ Float collar used _____ Btm 3 jts welded _____ | | | | | |
| TD of hole _____ Set _____ Feet of _____ Inch _____ # Grade _____ | | | | | |
| New-used csg. @ _____ with _____ sacks neat cement around shoe | | | | | |
| + _____ sax _____ additives _____ | | | | | |
| Plug down @ _____ (AM) (PM) Date _____ | | | | | |
| Cement circulated _____ No. of Sacks _____ | | | | | |
| Cemented by _____ Witnessed by _____ | | | | | |
| Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____ | | | | | |
| Casing test @ _____ (AM) (PM) Date _____ | | | | | |
| Method Used _____ Witnessed by _____ | | | | | |
| Checked for shut off @ _____ (AM) (PM) Date _____ | | | | | |
| Method used <i>CEMENT PLOGS VIA TUBING</i> Witnessed by <i>HOBBS</i> | | | | | |
| Remarks: _____ | | | | | |

Plugs as follows: mud between plugs.

1. T.D. 25 sks. — OK, 1-17-63 H.L.
2. 5050 25 sks. — OK, 1-17-63 H.L.
3. ~~4700~~ ³⁸⁸⁵ 25 sks. OK, 1-22-63, H.L.
4. 2768 25 sks. OK, 1-22-63, H.L.
5. 1158 25 sks. OK, 1-22-63, H.L.
6. 500 25 sks. OK, 1-22-63, H.L.
7. 30 ft. of cement + dry hole marker.