

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

AREA 640 ACRES
LOCATE WELL CORRECTLY

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

Simms & Reese Oil Co. Company or Operator **John Pedell**
Well No. **3** in **net of net** of Sec. **35** T. **18 S**
R. **26 E**, N. M. P. M., **Dayton** Field, **Eddy** County.
Well is **990** feet south of the North line and **990** feet west of the East line of **sec. 35**
If State land the oil and gas lease is No. **x** Assignment No. **x**
If patented land the owner is **John Pedell**, Address **Kansas City Kansas**
If Government land the permittee is **John Pedell**, Address **Kansas City, Kansas**
The Lessee is **John Pedell**, Address **Kansas City, Kansas**
Drilling commenced **July 15** 19 **51** Drilling was completed **Aug 25** 19 **51**
Name of drilling contractor **Myron Bruning**, Address **Artesia, N.M.**
Elevation above sea level at top of casing _____ feet.
The information given is to be kept confidential until _____ 19 _____

OIL SANDS OR ZONES

No. 1, from **1126** to **1138** No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
7	24	10	used	920	larkin			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto:

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

PRODUCTION

Put to producing _____ 19 _____
The production of the first 24 hours was **Dry (No Porosity)** barrels of fluid of which _____ % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, Be _____
If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
Rock pressure, lbs. per sq. in. _____

EMPLOYEES

_____, Driller _____, Driller
Earl McDorman, Driller _____, Driller
Louise Dundam

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Place _____ Date **Sept 14, 1951**
Name **Freddie Simms**
Position _____

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	26	26	surface
26	43	17	caliche and sand
43	64	21	water sand and gravel
64	75	9	" " "
75	181	102	gumbo and blue shale
181	225	44	blue shale
225	370	145	" " and gumbo
370	410	40	shale and anhydrite
410	497	87	sandy anhydrite
497	530	33	anhydrite
530	560	30	anhydrite and red clay
560	635	75	red clay anhydrite and shale
635	650	15	Water. Grey lime
650	665	15	grey lime -red bed
665	730	65	broken grey lime -Red shale
730	765	35	grey lime (probably water)
765	801	36	" " " "
801	815	14	" " " "
815	850	35	Red shale
850	876	26	grey lime Hard
876	902	26	Red shale Grey lime Broken
902	920	18	hard grey lime (set 7" pipe
920	960	40	sandy grey lime
960	980	30	lime hard
980	995	5	sandy (gas odor)
995	1028	grey lime	
1028	1045	17	lime (sandy)
1045	1052	7	sandy lime (oil stain)
1052	1066	14	lime (brown and grey)
1066	1080	14	mixed lime
1080	1084	4	sandy lime (odor of oil)
1084	1120	36	grey lime
1120	1126	6	sandy lime hard (odor)
1126	1138	12	grey sand(heavy stain) Cemented
1138	1144	6	pink & grey lime 40% shale 50% sand 10% } Heavy
1144	1157	13	lime 40% shale 20% sand 40% } Sand
1157	1162	5	80%lime 10%shale 10% sand
1162	1167	5	lime 40% sand 60% Loose
1167	1171	4	sand 100% loose Slt.Stu.F.Q.G.
1171	1201	30	Wht.Lime Fx.
1201	1207	6	wht. Fx. (Top San Andres) TD.