
	m 9. Feb. 1	<b>-331 a</b> 951)	L 		
A	-	نسا	30	)	VED
		MΑ	12	0 1	959
AG	R TIN	O D	к; <b>151</b> 1	f lG∓	VANS ENGINEER
1					

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY



## SUNDRY NOTICES AND REPORTS ON WELLS

WILLIE UP INTENTION TO DOUT		1 1	
		The state of the s	
NOTICE OF INTENTION TO CHANGE		STOCKING ON ACIDIZING	3 f 21
NOTICE OF INTENTION TO TEST WA		The state of the s	
NOTICE OF INTENTION TO RE-DRILI NOTICE OF INTENTION TO SHOOT O			
NOTICE OF INTENTION TO PULL OR			
NOTICE OF INTENTION TO ABANDON			
			X
(INDIC.	ATE ABOVE BY CHECK MARI	K NATURE OF REPORT, NOTICE, OR OTHER DATA)	
mesott & Durmey Fede	· ·	My 19, ,	9_ <b>59</b>
ell Nois loca	ted <b>330</b> ft. from	$\{ egin{array}{c} N \\ M \end{array} \}$ line and $\{ egin{array}{c} M \\ M \end{array} \}$ line of sec	36
(½ Sec. and Sec. No.)		(Range) (Meridian)	
reland mustacl		, ,	
(Field)	(County	or Subdivision) (State of Ferritory)	
st 0 5/3-22 surfac myball Drilling Com po NV30 - 8 5/8 2	o objective sands; show size ing points, and all company prior to a co	vel isft.  ILS OF WORK  zes, weights, and lengths of proposed casings; indicate mudding jobs, ce other important proposed work)  rested to live live lives, Roclinater, E.  running 5; - 15.56 casing. Run (uiberson)	P.
met 8 5/3-21; surface maybell Drilling Composition 2 5/3" 2 top of packer mand sok to i." Fil drill pressured up to 600%, sain to 650% and track? Welded casing oddial pressure 550%	o objective sands; show sizing points, and all composites as dispersy prior to a 2-40% X 23° passive a 6° x 23° ipe. Set packet pressure bled ced leak to 3 5° cliar and tight	ILS OF WORK  zes, weights, and lengths of proposed casings; indicate mudding jobs, ce other important proposed work)	P. i ilugg subs
maybell Drilling Composited By 10 - 8 5/8" 2 top of packer mand wak to he Fi first drill pressured up to 600%, and to 650% and track. Welded casing oddial pressure \$50% at in pressure at he at in pressure at 5	o objective sands; show sizing points, and all composites, and all composites are composited as a composite of the composite	ILS OF WORK  res, weights, and lengths of proposed casings; indicate mudding jobs, ce other important proposed work)  rested by in like Lynch, Tochpusher, E. running 5: - 15.55 casing. Ren Guiberson sker with bottom of pasker mandrel bull the Srd perferated mipple and necessary at at 95.13 and circulated 10 minutes. back to 100% in 2 minutes. Pressured up	P. i ilugg subs
set 8 5/3-21/ surface suppoli Drilling Composition of 5/3" 2 top of packer mend sek to 1 "Fil drill pressured up to 600%, sain to 650% and track?. Welded casing oddinal pressure at 1 at in pressure at 5 at in pressure at 5 at in time 30 minute.	o objective sands; show sizing points, and all composites, and all composites are considered as the composite of the composit	ILS OF WORK  Les, weights, and lengths of proposed casings; indicate mudding jobs, ce other important proposed work)  Lested by Mr. Mike Lynch, Coclapather, E. Running 5: 15.55 cessing. Ren Guiberson sker with bottom of packer mandrel bull MR 3rd perferated nipple and necessary at 253.13 and circulated 10 minutes, back to 100% in 2 minutes. Pressured up a casing collar below flamps and cate decorated flamps commentations.	P.
mybell Drilling Composition of Sold Sold Sold Sold Sold Sold Sold Sold	o objective sands; show sizing points, and all concentrations are dispersed by the same of	ils of work  rest, weights, and lengths of proposed casings; indicate mudding jobs, ce other important proposed work)  rested by hr. Kike Lynch, Tochpusher, E. running 5; - 15.55 casing. Ren Guiberson sker with bottom of pasker mandrel bull  DIE 8rd perferated mipple and necessary or at 951.18 and circulated 10 minutes. back to 1005 in 2 minutes. Pressured up // casing collar below flange and gate second flange commentions.	P.
set 8 5/3-21 surface supbell Drilling Compe 1830 - 8 5/3" 2 top of packer mend sek to he FM drill pressured up to 600%, sain to 650% and track. Welded casing oditial pressure 550% at in pressure at he in pressure at he in time 30 minute understand that this plan of work understand the plan of work under	o objective sands; show sizing points, and all concentrations are dispersed by the same of	ILS OF WORK  Les, weights, and lengths of proposed casings; indicate mudding jobs, ce other important proposed work)  Lested by Mr. Mike Lynch, Coclapather, E. Running 5: 15.55 cessing. Ren Guiberson sker with bottom of packer mandrel bull MR 3rd perferated nipple and necessary at 253.13 and circulated 10 minutes, back to 100% in 2 minutes. Pressured up a casing collar below flamps and cate decorated flamps commentations.	P. Subs
saybell Drilling Compension of Parish Surface Saybell Drilling Compension of Sold Saybell Drilling Compension of the Sold Saybell Sayb	o objective sands; show sizing points, and all controls as dispersy prior to a 2-10% X 23 page for a 60 x 23	ILS OF WORK  Les, weights, and lengths of proposed casings; indicate mudding jobs, ce other important proposed work)  Lested by Mr. Mike Lynch, Coclapather, E. Running 5: 15.55 cessing. Ren Guiberson sker with bottom of packer mandrel bull MR 3rd perferated nipple and necessary at 253.13 and circulated 10 minutes, back to 100% in 2 minutes. Pressured up a casing collar below flamps and cate decorated flamps commentations.	P. Subs
set 8 5/3-21 surface maybell Drilling Composition of packer mand sek to he will drill pressure to 600, and track to 650 and track welded casing oddial pressure 550 at in pressure at he in time 30 minute understand that this plan of work mpany R. P. Campbe.	o objective sands; show sizing points, and all concepts of the casing as directly party prior to a 2-to. I 23 page that a 6 x 25 page that a 6 x 2	ILS OF WORK  Les, weights, and lengths of proposed casings; indicate mudding jobs, ce other important proposed work)  Lested by Mr. Mike Lynch, Coclapather, E. Running 5: 15.55 cessing. Ren Guiberson sker with bottom of packer mandrel bull MR 3rd perferated nipple and necessary at 253.13 and circulated 10 minutes, back to 100% in 2 minutes. Pressured up a casing collar below flamps and cate decorated flamps commentations.	P. Subs
mybell Drilling Compension of Packer mand top of packer mand ok to he Fil drill pressured up to 600%, ain to 650% and track. Welded caming of this pressure at he in pressure at he in pressure at he in time 30 minute understand that this plan of work mpany R. P. Compbension 1603 Broaders	o objective sands; show sizing points, and all concepts of the casing as directly party prior to a 2-to. I 23 page that a 6 x 25 page that a 6 x 2	ILS OF WORK  Les, weights, and lengths of proposed casings; indicate mudding jobs, ce other important proposed work)  Lested by Mr. Mike Lynch, Coclapather, E. Running 5: 15.55 cessing. Ren Guiberson sker with bottom of packer mandrel bull MR 3rd perferated nipple and necessary at 253.13 and circulated 10 minutes, back to 100% in 2 minutes. Pressured up a casing collar below flamps and cate decorated flamps commentations.	P.