

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

JUN -4 1987

O. C. D.

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON OIL AND GAS WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-DRILL A WELL IN A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- P&A	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name Martin
3. Address of Operator 105 South 4th St., Artesia, NM 88210	9. Well No. 1
4. Location of Well UNIT LETTER N 660 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 15 TOWNSHIP 18S RANGE 26E NMPM.	10. Field and Pool, or Wildcat Atoka San Andres
15. Elevation (Show whether DF, RT, GR, etc.) 3345' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plugged and abandoned well as follows:

RUPU. Laid down polish rod, 68 - 5/8" rods and pump. Set CIBP at 1700'.  
Circulated with brine gel. Spot 25 sx cement on CIBP.  
Spot 35 sx at 1148-803'.  
WIH and perforated 4 holes at 750'. Install plug container.  
Cement 5-1/2" x 8-5/8" annulus with 135 sx Class "C" with 3% Cacl2.  
Circulate to surface. WOC 2 hrs. Tagged plug at 336'.  
Spot 10 sx cement plug from 30' to surface.  
Install dry hole marker.  
Plugging completed 6-1-87.

Post ID-2  
6-12-87  
P&A

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Janita Goodlett TITLE Production Supervisor DATE 6-2-87

APPROVED BY Mike Steelfield TITLE OIL AND GAS INSPECTOR DATE JAN 11 1988

CONDITIONS OF APPROVAL, IF ANY: