

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/ ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED

NEW MEXICO OIL CONSERVATION COMMISSION

NOV 20 1969

O. C. C.
ARTEBIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name Atoka San Andres Unit
2. Name of Operator Kewanee Oil Company ✓	8. Farm or Lease Name Tract 20
3. Address of Operator P. O. Box 3786, Odessa, Texas 79760	9. Well No. 1
4. Location of Well UNIT LETTER B , 330 FEET FROM THE North LINE AND 2310 FEET FROM THE East LINE, SECTION 13 TOWNSHIP 18S RANGE 26E NMPM.	10. Field and Pool, or Wildcat Atoka San Andres
15. Elevation (Show whether DF, RT, GR, etc.) 3294' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER Convert to Water Injection Well <input checked="" type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Pull rods and tubing, clean out to TD of 1765' and wash hole down with 250 gallons acid. Set tension packer at approximately 1630' on 2-3/8" O. D. tubing coated internally with plastic and load annulus with inhibited water. Start fresh water injection down tubing at rate of about 200 BPD. Injection will commence on or about 1-1-70.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. F. Stuckert TITLE Division Superintendent DATE 11-18-69

APPROVED BY W. A. Gressett TITLE Oil and Gas Supervisor DATE NOV 21 1969

CONDITIONS OF APPROVAL, IF ANY: