

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED
 NEW MEXICO OIL CONSERVATION COMMISSION
FEB 17 1970
O. C. C.
ARTESIA, OFFICE

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name Atoka San Andres Unit
2. Name of Operator Kewanee Oil Company	8. Farm or Lease Name Tract 20
3. Address of Operator P. O. Box 3786, Odessa, Texas 79760	9. Well No. 1
4. Location of Well UNIT LETTER B 330 FEET FROM THE North LINE AND 2310 FEET FROM THE East LINE, SECTION 13 TOWNSHIP 18S RANGE 26E NMPM.	10. Field and Pool, or Wildcat Atoka San Andres
15. Elevation (Show whether DF, RT, GR, etc.) 3294' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER Converting to Water Injection Well <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Pulled rods and tubing. Cleaned out to 1762' GR. Dumped 500 gallons diesel down casing followed by 250 gallons 15% regular acid. Ran 5-1/2" tension packer on 2-3/8" tubing coated internally with plastic. Loaded annulus with inhibited water and set packer at 1624.96' GR. Started water injection 1-29-70. Well accepting 255 barrels water per day at 350 psi.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. J. [Signature] TITLE Division Superintendent DATE 2-12-70

APPROVED BY B. J. [Signature] TITLE OIL AND GAS INSPECTOR DATE FEB 17 1970

CONDITIONS OF APPROVAL, IF ANY: