

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

STANDARD OIL COMPANY OF TEXAS

Ralph Rogers, et al

(Company or Operator)

(L-200)

Well No. 2, in E $\frac{1}{4}$ of SE $\frac{1}{4}$, of Sec. 10, T. 18N, R. 26E, NMPM.
Undesignated Eddy

Well is 330 feet from East line and 1650 feet from South line
of Section 10 If State Land the Oil and Gas Lease No. is - - -

Drilling Commenced.....October 28....., 19⁵⁶..... Drilling was Completed.....November 11....., 19⁵⁶.....

Name of Drilling Contractor.....Waters Drilling Company, Inc.

Address P. O. Box 144, Artesia, New Mexico

Elevation above sea level at Top of Tubing Head..... 3330'..... The information given is to be kept confidential until
- - -
..... 19.....

No. 1, from 1518	to 1531	No. 4, from 1693	to 1706
No. 2, from 1591	to 1604	No. 5, from	to
No. 3, from 1654	to 1672	No. 6, from	to

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from	Surface	to	1200, not tested	feet.
No. 2, from		to		feet.
No. 3, from		to		feet.
No. 4, from		to		feet.

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8	24 - 28	New	1192	Larkin float	None	None	Surface string
5 1/2	14	New	1713	Larkin float	None	1668-1651	Oil string

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11	8 5/8	1204	150	Pump and plug	10 lb. per gal.	Hole full
7 7/8	5 1/2	1723	250	Pump and plug	9 lb. per gal.	Hole full

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Acid washed perforated interval 1648-1651 with 500 gallons of mud acid and fractured with 10,000 gallons of gelled crude and 15,000 pounds of sand.

Result of Production Stimulation.....Flow 101 barrels oil in 24 hours at 14/64 choke, IP 230 psi, OP 350 psi.

Depth Cleaned Out.....1718

CORD OF DRILL-STEM AND SPECIAL TV

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from Surface feet to 1724 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing November 11, 1956
OIL WELL: The production during the first 24 hours was 101 barrels of liquid of which 99.8% was oil; % was emulsion; % water; and 0.2% was sediment. A.P.I. Gravity 38.7
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy.			T. Devonian		T. Ojo Alamo
T. Salt.			T. Silurian		T. Kirtland-Fruitland
B. Salt.			T. Montoya		T. Farmington
T. Yates			T. Simpson		T. Pictured Cliffs
T. 7 Rivers			T. McKee		T. Menefee
T. Queen			T. Ellenburger		T. Point Lookout
T. Grayburg			T. Gr. Wash		T. Mancos
T. San Andres	951		T. Granite		T. Dakota
T. Glorieta			T.		T. Morrison
T. Drinkard			T.		T. Penn.
T. Tubbs			T.		T.
T. Abo			T.		T.
T. Penn.			T.		T.
T. Miss.			T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
-0-	10	10	Kelly bushing to ground				
10	350	340	Sand and gravel				
350	725	375	Dolomite and sand				
725	1137	412	Dolomite				
1137	1471	334	Dolomite and anhydrite				5
1471	1622	151	Dolomite and shale				
1622	1724	102	Dolomite				1
							2
							1
							1

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator Standard Oil Company of Texas Address Bin B, Royalty, Texas
Name J. M. McMahan Position or Title District Engineer
Nov. 19, 1956 (Date)