## NEW MEXICO OIL CONSERVATION COMMISSION DRAWER DD ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Eupp. 1-9-85

		·							
Operator RALPH NIX			Lease	Lease CHAD				Well #/	
Location of Well	Unit P	Section 26		Townshi 'B		Range 26	County Eddy		
Drilling Contractor N/A Type of Equipment Rotary									
* = csg. то	WITNESS						1		
APPROVED CASING PROGRAM									
Size of Hol			Weight Per Foot		New	or Used	Depth	Sacks Cemen	
* 12.14			3 #		NEW	950	550 cm		
77/8		51/2	19	15.5		is .	3900'	700 circ	
		·							
Casing Data	:					· · · · · · · · · · · · · · ·			
Surfacejoints ofinch# Grade									
(Approved) (Rejected)									
Cementing P	-				·				
Size of hol	e 12/4	Size of C	asing	1% S	acks	coment r	equired	2012	
Size of hole 12/4 Size of Casing 174 Sacks coment required 200 Type of Shoe used Tex-At Float collar used Insert Btm 3 jts welded <u>Ves</u>									
TD of hole 954 Set 654 Feet of VD Inch at # Gnade = ==									
New-used csg. @ $454$ with 200 sacks neat cement around shoe									
+ 350 sax Heuro lite additives <u>1/4 Flafal 2%CC</u>									
Plug down @ 2:00 (AM) (@A) Date 7-18-54									
Cement circulated yer No. of Sacks 175									
Cemented by Hours Witnessed by Bulliour									
Survey ran @(AM) (PM) Datetop cement @									
Casing test	0	(AM) (P	M) Dat	······		cop_cen		× .	
Casing test @(AM) (PM) Date Method UsedWitnessed by									
Checked for	shut off	@ (AM)	) (PM)	Date	7956				
Method used				Witne	sed	by.		·····	
Remarks:	hast Dr	ila Break @	713				······································		
Remarks:hast Drilg Break @ 723									
	:						•		