

OPERATOR

Est. of Fred Turner, Jr.

DISTRICT

Empire ABO

LEASE

STATE H

1

WELL NO. 200111-1

Eddy Co. N. Mexico

Flange on head 6" 900 (STARR Tool Hobbs)

OCT in Hobbs has head 7" to 4 1/2" to 2 3/8"

10 3/4 CSA 975 cmt circ.

DATUM: 13' Above G.L.

5500

5600

5700

5800

5586

4/ft.

5602

5624

4/ft.

5642

5756

5763

2/ft.

5783

PBD 5784

CO. TO

5784

7" 23 CSA 5865'

DRILL
New
hole



@ Run 4 1/2" 10.5" circ to surface.

18" 111	5700.54
Sealing supply 1 1/2"	1.10
Baker R Pkg (iron ")	1.80
Post sub	3.05
sub	6.03
sub w/ P. 10/14	7.93
	41

5732.86

Propose To Deepen, Run 4 1/2" 10.5", Re-complete.

Use 6 1/8" bit drill to shale section, 6.125" bit
7" 23" I.D. 6.241"

4 1/2" 10.5" O.D. 5.00", I.D. 3.927 drill dia

7" 23" .2210 ft³/ft 4.524 ft/ft³

4 1/2" 10.5" .0895 " 11.167 "

Annulus 7" 4 1/2" .1106 ft³/ft 9.043 ft/ft³

6 1/8" hole 4 1/2" cdy. .0442 ft³/ft 10.6842 ft/ft³

6 1/8" hole .2046 ft³/ft 4.8872 ft/ft³

BAKER Model R Ret. Double Grip
11000 # 607" OD 17X 7"

Use 10 BFW + 1 gal MOR-flu ahead of 3Q on perfs.

3Q 75ss class "C" .8 halid 9 142" 1.5 ft³/sx.

50sx. " "C" 6" salt + 5" sand/sx 1.35 ft³/sx.

MIDLAND 563-2323

ODESSA 563-2323

OKLA. CITY 631-1129