

Dec. 1973

Budget Bureau No. 42-R1424

c/sf

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

OCT 10 1985

G. C. D.

ARTESIAN

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐2. NAME OF OPERATOR ARCO Oil and Gas Company
Division of Atlantic Richfield Company ✓3. ADDRESS OF OPERATOR
P. O. Box 1710, Hobbs, New Mexico 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 330' FSL & 2310' FWL (Unit N)

AT TOP PROD. INTERVAL: as above

AT TOTAL DEPTH: as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☒(other) ☐

5. LEASE

NM-7720

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

West Red Lake Unit

9. WELL NO.

30

10. FIELD OR WILDCAT NAME

Red Lake Queen Grbg

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

4-18S-27E

12. COUNTY OR PARISH 13. STATE

Eddy

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3559' DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to P&A in the following manner: MIRU, POH w/pump & rods. POH w/tbg. Run CBL to determine TOC. GIH OE & spot Class H cmt w/2% CaCl₂ across perfs 2017-2114'. WOC. Tag plug or cmt under cmt retr. Circ well bore w/9.5 ppg BW cont'g 25# gel/bbl. Perf above TOC as determined by CBL & break circ. Set cmt retr above perfs & circ &/or cmt squeeze formation. Dump 5 sx cmt on cmt retr. ① Spot mud in csg & 5 sx cmt @ surf. Cut off WH. Weld on regulation dry hole marker. Clean & level location.

① 100' plugs at:
1451'
565'
300'

Subsurface Safety Valve: Manu. and Type

Set @

Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

D. L. Shackelford

TITLE Engrg Tech. Spec. DATE

7/24/85

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: