

RECEIVED BY  
Dec. 1973

MAR 14 1985

O. C. D.  
ARTESIA, OFFICE

NM OIL CONS. COMMISSION

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY  
Drawer DD  
Artesia, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED BY

1. oil ☐ gas ☒ other

MAR 03 1986

2. NAME OF OPERATOR

EXXON CORPORATION O. C. D.

3. ADDRESS OF OPERATOR

Box 1600, MIDLAND, TEXAS 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2055' FSL & 1980' FWL OF SEC  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

5. LEASE

LC-026874E

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

CHALK BLUFF DRAW UNIT

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

RED LAKE PENN.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC 5 T-18-S, R-27-E

12. COUNTY OR PARISH

EDDY

13. STATE

NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3512' DF

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☒

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. INSTALLED BOP-TESTED TO 2000 PSI. KILLED WELL W/BRINE.
2. PULLED TUBING. SET BP IN PKR AT 9205'. RI 14 TO 9200'. SPOT 14 SX CMT DN PKR.-TOC 9140'. SPOT 25 SX PLUG AT 6220'. TOP OF CMT 6006'. SPOT 25 SX AT 4900'-TOC 4670'. SPOT 25 SX PLUG AT 3070'-TOC 2780'. SPOT 25 SX PLUG AT 1300'-TOC 1147'. SPOT 25 SX PLUG AT 610'-TOC 450'. SPOT 50 SX PLUG AT SURFACE.
3. INSTALLED DRY HOLE MARKER - CLEANED & LEVELED LOCATION.

Post ID: 3-22-85 P47

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

A. R. Lowe

TITLE

S.R. ADMIN.

DATE

3-11-85

(This space for Federal or State office use)

APPROVED BY

[Signature]

TITLE

DATE

2-28-84

CONDITIONS OF APPROVAL, IF ANY: