

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION
FEB 12 1970

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

O. C. C.
ARTESIA, OFFICE

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		7. Unit Agreement Name West Red Lake Unit
2. Name of Operator Atlantic Richfield Company		8. Farm or Lease Name West Red Lake Unit
3. Address of Operator P. O. Box 1978, Roswell, New Mexico 88201		9. Well No. 6
4. Location of Well UNIT LETTER K 2460 FEET FROM THE South LINE AND 2580 FEET FROM THE West LINE, SECTION 7 TOWNSHIP 18-S RANGE 27-E NMPM.		10. Field and Pool, or Wildcat Red Lake-Grayburg S.A.
15. Elevation (Show whether DF, RT, GR, etc.) 3294' Ground		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

To prepare this well for waterflood response, we propose to add Premier perforations from 998-1007' w/2 JSPF and treat w/500 gallons 15% HCl acid and 12,000 gallons of slick fresh water containing 12,000# of 20/40 sand. Work will start about 3/1/70.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *A. D. Lutchas*

Dist. Drlg. Supervisor

2-10-70

APPROVED BY *W. A. Gressett*

TITLE OIL AND GAS INSPECTOR

DATE FEB 12 1970

CONDITIONS OF APPROVAL, IF ANY: