

Dec. 1975

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Artesia, NM 88220

## SUNDY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR ARCO Oil and Gas Company  
Division of Atlantic Richfield Company

3. ADDRESS OF OPERATOR  
P. O. Box 1710, Hobbs, New Mexico 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 986' FNL & 1648' FEL (Unit B)  
AT TOP PROD. INTERVAL: as above  
AT TOTAL DEPTH: as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☒

(other)

5. LEASE

LC 054205

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

West Red Lake Unit

9. WELL NO.

22

10. FIELD OR WILDCAT NAME

Red Lake Grayburg SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

8-18S-27E

12. COUNTY OR PARISH 13. STATE

Eddy

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

Unknown

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Propose to P&A in the following manner: MIRU, check for pressure. POH w/pump & rods. POH w/tbg. Attempt to PU & POH 5" csg. Spot Cl H cmt cont'g 2% CaCl<sub>2</sub> 1200' TD to surface if 5" is pulled. If unable to pull 5", perf @ 1000'. Break circ. Set cmt retr @ approx 975', circ cmt behind 5". Dump 5 sx on cmt retr. Circ hole w/9.5 ppg gel BW cont'g 25# gel/bbl. Spot 10 sx cmt plug @ surface. Cut off WH, weld on regulation dry hole marker. Clean & level location for abandonment.

① 100' plug at 730' + 300'

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED D. L. Shackelford TITLE Engrg Tech Spec. DATE 7/24/85

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE 10-9-85  
CONDITIONS OF APPROVAL, IF ANY: