

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN DUPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-025604

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL ☒ WELL GAS ☐ WELL OTHER ☐

2. NAME OF OPERATOR

PAN-AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

Box 68, Hobbs, N. M.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

14. PERMIT NO.

15. ELEVATIONS (Show whether SF, RT, OR, etc.)

3547' R.D.B.

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

MALCO G. FEDERAL

9. WELL NO.

10

10. FIELD AND POOL, OR WILDCAT

EMPIRE A50-

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

9-18-27 NMPM

12. COUNTY OR PARISH

EDDY N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

In accordance w/ Form 9-331 submitted 9-13-66,
remedial work performed as follows:

Perforated 4 1/2" casing at 5400-01 w/ 1455. Set. Ret. BP
@ 5450', capped w/ 10' sand. Squeezed behind 4 1/2" casing
w/ 20004 Sulcor w/ Halad 9. Drilled and cleaned
out to PBD of 5664'. Acidized perforations (perforated
5496-5504, 19-30, 42-58, 77-87 w/ 25SP) w/ 2000 gal 15%
and 3000 gal 28%. Evaluated and restored
to production.

Prior - well had a 22 BOPD penalized allow.
after - flow 2960 x 0 BW 24 hrs. 8028500.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Sup

DATE

10-12-66

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL

TITLE

DATE

0+4- USGS- ART-
1- NSW
1- SUSP
1- RRY
1- HONDO

APPROVED
OCT 14 1966
R. L. BEEKMAN
ACTING DISTRICT ENGINEER

See Instructions on Reverse Side

RECEIVED
OCT 13 1966
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO